

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:      Fraction      Section Number      Township Number      Range Number  
COUNTY: FORD      NE 1/4 SE 1/4 SW 1/4      11      T 27 S      R 21 W

Distance and direction from nearest town or city street address of well if located within city?  
10 MILES NORTH, 2.5 MILES EAST OF BUCKLIN

2 WATER WELL OWNER:      KATHRYN SUGHRUE ESTATE      Board of Agriculture, Division of Water Resources  
RR#, St. Address, Box # :      Application Number:        
City, State, ZIP code : ULYSSES, KS 67880-

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:      4 DEPTH OF COMPLETED WELL      20 ELEVATION: 0  
Depth(s) Groundwater Encountered      1. 0 ft.      2. 0 ft.      3. 0 ft.      0 ft.

|   |     |     |     |     |     |
|---|-----|-----|-----|-----|-----|
| 1 | --- | NW  | --- | NE  | --- |
| M | W   | --- | --- | --- | E   |
| i |     | --- | --- | --- |     |
| l |     | --- | --- | --- |     |
| e |     | --- | --- | --- |     |
|   |     | SW  | X   | SE  |     |

WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 03/13/06  
Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm  
Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm  
Bore Hole Diameter 8.75 in. to 20 ft., and in. to 0 ft.  
WELL WATER TO BE USED AS: LIVESTOCK  
Was a chemical/bacteriological sample submitted to department? No ;  
If yes, mo/day/yr sample was submitted      Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC      CASING JOINTS: GLUED  
Blank casing diameter 5 in. to 10 ft., Dia in. to 0 ft., Dia in. to 0 ft.  
Casing height above land surface 12 in., weight 0 lbs/ft. Wall thickness or gauge No. 26  
TYPE OF SCREEN OR PERFORATION MATERIAL: PVC  
SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

|                              |                        |                     |
|------------------------------|------------------------|---------------------|
| SCREEN PERFORATED INTERVALS: | From 10 ft. to 20 ft., | From 0 ft. to 0 ft. |
|                              | From 0 ft. to 0 ft.,   | From 0 ft. to 0 ft. |
| GRAVEL PACK INTERVALS:       | From 10 ft. to 20 ft., | From 0 ft. to 0 ft. |
|                              | From 0 ft. to 0 ft.,   | From 0 ft. to 0 ft. |

6 GROUT MATERIAL BENTONITE  
Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
What is the nearest source of possible contamination: SEPTIC TANK      How many feet? 5000  
Direction from well? WEST

| FROM | TO | LITHOLOGIC LOG  | FROM | TO | PLUGGING INTERVALS |
|------|----|-----------------|------|----|--------------------|
| 0    | 3  | SILT AND SAND   |      |    |                    |
| 3    | 18 | SAND AND GRAVEL |      |    |                    |
| 18   | 20 | TAN CLAY        |      |    |                    |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 03/13/06 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 653      This Water Well Record was completed on (mo/day/yr) 06/28/06  
under the business name of DAN HAYSE WATER WELL SERV      by (signature) Dan Hayse