WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | | | | | | | горека, каг | isas 00020 | | |
|--|--|---|-----|----------------|---------|---|---|--|----------------|--|
| 1 location of well | County Fraction | | | Section number | | Township number Range number | | | | |
| 1. Location of well: | Ford | SW 1/4 NTE 1/4 NV | 1/4 | 18 | | ↑ 27 | S R | 22 | E/W | |
| 2. Distance and direction from nearest town or city: 4 mi. N of Ford 3. Owner | | | | | · Fo | ord County Lar | ıd & Ca | ttle C | o. | |
| Street address of well location if in city: City, state, zip code: FC | | | | | | and Ke 678 | U. 4 2 | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | F*C | 6. Bore hole dia. 16 in. Completion date | | | | |
| N | | | | | | Well depth 387 ft. 8/26/76 | | | | |
| 40' East of pivot | | | | | | 7 Cable tool _X Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary | | | | |
| | | | | | | 8. Use: Domestic Public supply Industry | | | | |
| w | | | | | | ▼ Irrigation Air conditioning Stock | | | | |
| sw se | | | | | | LawnOil field waterOther 9. Casing: Material _steel; Height: (Above) or below | | | | |
| | | | | | | Threaded Welded Surface12 in. | | | | |
| S | | | | | | RMPPVCWeight 36.86_lbs./ft. Dia 16_in. to 387 ft. depth Wall Thickness; inches or | | | | |
| 1 ← 1 Mile → 1 5. Type and color of material | | | | From | То | Dia.16_in. to 30.4 ft. Diain. toft. | depth wall | No21 | 9 | |
| 5. Type and color of | | | | 1.0 | | 10. Screen: Manufacture | | | | |
| sand. gvo | | | | 0 | 70 | Lakewood Type Millslot | Dia | 16" | | |
| | _ | | | 1. | | Slot gauze 1/8 x | 🚖 Lengti | ь <u>201 </u> | | |
| sand, grav | el | | - | 140 | 60 | Set between 37 | | 118 387 | ft. | |
| gyp, sand | | | | 60 | 80 | Gravel pack? yes Siz | | iaterial | x 1 | |
| sand rock | | | | 80 | 100 | 11. Static water level: mo./day/yr. 33 ft. below land surface Date 7/27/76 | | | | |
| sand, clay balks | | | | 100 | 140 | 12. Pumping level below | | |)_ g.p.m. | |
| sticky clay | | | | 140 | 280 | ft. after hrs. pumping g.p.m. | | | | |
| sandstone | A series of the | managan menengan dan dianggan dan sebagai | | 280 | 387 | 13. Water sample submit | | mo | g.p.m. | |
| The graph property and the second | The second secon | | | 1 | | Yes y No | Date | | | |
| to the state of th | | | | + | | Well head completion Pitless adapter | | Inches above | e grade | |
| | | | | | | 15. Well grouted? Ye | | | 3 | |
| | | , t | ۴ | 1 | | With: Neat cement | Bento | | Concrete | |
| | and a second sec | | | . 7 | | Depth: From ft 16. Nearest source of po | | | | |
| | | | | - | | ft Direction | | Type | | |
| | | | | | | Well disinfected upon co | | Yes _ Not installed | No | |
| | | | | | | 17. Pump: Manufacturer's name | <i>lorthi</i> | | : | |
| | | | | | | Model number 7S-12 | И90 нр _ | Vo | olts | |
| | | | | | | Length of drop pipe 32 Type: | ft. c | apacity 900 | 4-g.p.m. | |
| | | | | ļ | | Submersible | | X_ Turbin | | |
| (Use a second sheet if needed) | | | | | | Jet Centrifugal | | Recipr | rocating | |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contract | | | | |
| | | | | | | This well was drilled und | | | is report | |
| Topography: | graphy: High Plains | | | | | | is true to the best of my knowledge and belief. Drilling & Supply. Inc. 136A | | | |
| Hill | | Business name | | | Sus No. | | | | | |
| X Slope 402 North T | | | | | | Signed Bot D & Hubrer Dat 8-3/ | | | | |
| Valley | | | | | | Signed Authorize | representat | ive Date | , — | |