USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY. BUCKLINI NW

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

		· 1/				Тор	eka, Kansas 66620		
	County Fraction			Section number		Township number	Range number	ige number	
1. Location of well:	Ford	1/4 NE 1/4 NE	1/4	29		T 27 S	R 22	E ⊘	
2. Distance and direction from nearest town or city: 3/4 N Ford				er of well: Ford County Feedyard					
Street address of well location if in city:					street: Ford, Ks. 67842				
4. Locate with "X" in sec	etian halow.	Sketch map:	City, s	itate, zip	code:	6. Bore hole dia. 24 in	Completion date	0/5/78	
N	chon below:	skeren map.				Well depth 144 ft.	- Comprehending and 2		
Ī []						7 Cable tool X_ Rotary	. —		
NW	NE					Hollow rod Jetted			
× V I	i E					8. Use: Domestic F	Public supply In Air conditioning 🗶 S		
ī '						Lawn C			
sw	1							, ,	
<u>!</u>	_!					Threaded Welded RMP PVC		in. ibs./ft.	
1-4	 +1 ,					Dia.16 in. to 144ft. de	pth Wall Thickness: i		
5. Type and color of mate	erial			From	То	Dia in. to ft. dep 10. Screen: Manufacturer's	***************************************	_	
					20	Lakewood			
Sandy clay.	gyp		r	0	20	Type Millslot Slot/gauze 1/8 x 2	Dia. 16"		
Sandy clay,	gyp			20	40	Set between <u>84</u>	_ft. and <u>144</u>	ft.	
Clay 14+75 sandstone				40	60	Gravel pack? X Size re	and	x 3/8	
Clay sandstone				(60)	80	11. Static water level:		o./day/yr.	
Clay, sands	tone	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	೧೨	(00)	00		rface Date <u>8-14</u>	<u> </u>	
Sandstone	Management and the second of t		7	80	120	12. Pumping level below lar 137 ft. after 8	d surfaces:		
Sandstone	And the state of t	the state of the s	3	120	135	ft. after	hrs. pumping		
Clay	Andread the production was also recognized to		/ '	135	144	Estimated maximum yield —	400	g.p.m.	
and the same of th	Mar. Sp.A	100 100 W		+		13. Water sample submitted: YesX_ No	Date	o./day/yr.	
	Ald and	* 5 W o		ļ		14. Well head completion:			
and the space of t	BROCK	60' shomes					12 Inches above	grade	
		54	,			15. Well grouted? X	BentoniteX	Concrete	
	a file of the	<u></u>		+		Depth: From 0 ft. to	1 ()		
	7 () () () () () () () () () (O satisfaction	:		ļ	16. Nearest source of possib ft Direction	le contamination:	<u> </u>	
		y =	. · · ·			Well disinfected upon compl		X No	
	`			1		17. Pump:	Not installed thington		
14 C			1		Manufacturer's name WOI Model number 121-40-	35HP V	olts		
						Length of drop pipe 130	ft. capacity 37	5 _{g.p.m.}	
						Type: Submersible	X Turbir	.	
				1		Jet	Recip	rocating	
10 [<u> </u>	heet if needed)		<u> </u>	i	Centrifugal	Other	·	
18. Elevation: 19.	Remarks: Feedlot suppl:	v well				20. Water well contractor's This well was drilled under n		is report	
Tanagraphy		1				is true to the best of my know	wledge and belief.	136 A	
Topography: ,	741	12 MOHD				High Plains I Business name		cense No.	
Slope	271) (")				Address 5310 W. H	iway 50 G	C. Ks	
Upland	. 6	0				Signed By D Harby	zesi Date	-30-78	