LOCATION OF WATER WELL: COUNTY: 029 FORD					-		_	
	NN 1/4 NN 1/4	NW 1/4	; 31	:	T 27	S	; R 23	₩
Distance and direction from (APPROX. 7 MILES EAST & 3/4 M	ILES NORTH OF DODGE CIT	ΤΥ.			·			
WATER WELL OWNER: AI RR#, St. Address, Box # ;					ulture, Di			
City, State, ZIP code : F(ORD, KS 67842-		Appli	ication Nu				
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	; 4 DEPTH OF (Depth(s) 6							
X ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	WELL'S STAT: 	IC WATER LEVEL ump testdata:	53 ft. bel Well water wa	low land s	urface mea ft. after	sured on hou	mo/day/yr rs pumping	
	; ; Estimated Y:						rs pumpin	}
W	E Bore Hole Di	iameter :	10 in. to	270 ft.	, and	in. to	ft.	
; SW SE -		TO BE USED AS: (01 DOMESTIC					
	; ; Was a chemic ; ; If yes, mo/o	cal/bacteriolog: day/yr samole w	ical sample s as submitted	submitted			ell disin	fected?
YPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surf	PVC (5 in. to 270 ft., face 12 in., we	CASING JOINTS: (GLUED to ft.		in. to	 ft		
YPE OF BLANK CASING USED: OZ Blank casing diameter Casing height above land surf YPE OF SCREEN OR PERFORATION CREEN OR PERFORATION OPENING	PVC (5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC (S ARE: 03 MILL SL(CASING JOINTS: (Dia in. Pight 3 lbs.	 GLUED to ft.		in. to	 ft		
IYPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surf IYPE OF SCREEN OR PERFORATION CREEN OR PERFORATION OPENING	PVC (5 in. to 270 ft., face 12 in., we N MATERIAL: 07 PVC SS ARE: 03 MILL SLO	CASING JOINTS: (Dia in. Pight 3 lbs: OT t. to 270 ft.	GLUED to ft. /ft. Wall th	, Dia nickness o	in. to r gauge No ft.	 ft		
YPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surr EYPE OF SCREEN OR PERFORATION COREEN OR PERFORATION OPENING COREEN PERFORATED INTERVALS:	PVC (5 in. to 270 ft., face 12 in., we will be a second to the second t	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft.	GLUED to ft. /ft. Wall th , From	, Dia nickness o ft. to ft. to	in, to r gauge No ft, ft,	 ft		
YPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surf YPE OF SCREEN OR PERFORATION CREEN OR PERFORATION OPENING	PVC (5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC GS ARE: 03 MILL SLO From 210 ft From 210 ft From 20 ft	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft., t. to 270 ft., t. to 270 ft.,	GLUED to ft. /ft. Wall th , From , From , From	, Dia nickness o ft. to ft. to	in. to r gauge No ft.	 ft		
YPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surg EYPE OF SCREEN OR PERFORATION CREEN OR PERFORATION OPENING CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONI	PVC (5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC (6 ARE: 03 MILL SLC) From 210 ft From	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to 5t. t. to 270 ft. t. to ft.	GLUED to ft. /ft. Wall th , From , From , From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft265		
FOR PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONIT GROUT Intervals: GROUT Intervals: GROUT Intervals: GROUT Intervals: GROUT Intervals: From 2	PVC (5 5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC (6 S ARE: 03 MILL SLC (6 From fill Fro	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to ft. t. to 270 ft. t. to ft.	GLUED to ft. /ft. Wall th , From , From , From , From	, Dia nickness o ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	 ft		
FORT MATERIAL 03 BENTONIA GROUT MATERIAL 03 BENTONIA GROUT Intervals: FROUT Intervals: FROUT Intervals: GROUT Intervals: FROUT Intervals: From 2 Heat is the nearest source of	PVC (5 5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC (6 S ARE: 03 MILL SLC (6 From fill Fro	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to ft. t. to 270 ft. t. to ft.	GLUED to ft. /ft. Wall th , From , From , From , From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.		
YPE OF BLANK CASING USED: 02 Plank casing diameter Plank casing height above land surf PREOF SCREEN OR PERFORATION OPENING PERFORATION OPENING PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONING POUT Intervals: From 2 Plant is the nearest source of pirection from well? FROM ; TO ;	PVC (5 5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC (6 S ARE: 03 MILL SLC (6 From fill Fro	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to ft. t. to 270 ft. t. to ft.	GLUED to ft. /ft. Wall th , From , From , From , From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.		feet?
YPE OF BLANK CASING USED: 02 Plank casing diameter Casing height above land surre CYPE OF SCREEN OR PERFORATION COREEN OR PERFORATION OPENING COREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONIA FROM Intervals: From 2 Control of the searest source of the searcest source sources sources sources source sources source sources sources source sources	PVC (Company) From 210 ft From 210 ft From 20 ft From 61	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to ft. t. to 270 ft. t. to ft.	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?
FROM: TO: TYPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surrest of screen or perforation opening GCREEN OR PERFORATION OPENING GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: FROM Intervals: From 2 Control of the screen of the scre	PVC (5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC (SS ARE: 03 MILL SLO From 210 ft (From 60 ft (Fr	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to ft. t. to ft. t. to ft.	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?
FROM: TO: TYPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surrest of screen or perforation opening GCREEN OR PERFORATION OPENING GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: FROM Intervals: From 2 Control of the screen of the scre	PVC (Company) From 210 ft From 210 ft From 20 ft From 61	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to ft. t. to ft. t. to ft.	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?
TYPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surf TYPE OF SCREEN OR PERFORATION BCREEN OR PERFORATION OPENING CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONIT Grout Intervals: From 2 What is the nearest source of Direction from well? FROM : TO :	PVC (5 in. to 270 ft., face 12 in., we haterial: 07 PVC (SS ARE: 03 MILL SLO From 210 ft From ft Fr	CASING JOINTS: (Dia in. eight 3 lbs. OT t. to 270 ft. t. to ft. t. to ft. t. to ft. COARSE SAND	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?
TYPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surf TYPE OF SCREEN OR PERFORATION OPENING CREEN OR PERFORATION OPENING CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONING FOOT INTERVALS: GROUT MATERIAL 03 BENTONING FOOT INTERVALS: FROM : TO :	PVC (Formula to the second of	CASING JOINTS: (Dia in. eight 3 lbs. DT t. to 270 ft. t. to 170 ft. t	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?
FROM TO TO THE STATE OF THE STA	PVC (5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC SS ARE: 03 MILL SLO From 210 ft From ft From 20 ft From ft From ft From 20 ft From ft ARE to 20 ft., From ft LITHOLOGIC LOG CLAY SAND OB MEDIUM SAND 14 CLAY SAND OB MEDIUM SAND 13	CASING JOINTS: (Dia in. eight 3 lbs. DT t. to 270 ft. t. to 170 ft. t	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?
TYPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONIO Screen of Direction from well? FROM : TO :	PVC (5 in. to 270 ft., face 12 in., we MATERIAL: 07 PVC (SS ARE: 03 MILL SLO From 210 ft From ft From 20 ft From ft From ft From 10 ft From	CASING JOINTS: (Dia in. eight 3 lbs. DT t. to 270 ft. t. to 170 ft. t	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?
TYPE OF BLANK CASING USED: 02 Blank casing diameter Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONIO BOTOLI Intervals: From 2 What is the nearest source of Direction from well? FROM : TO :	PVC (5 in. to 270 ft., face 12 in., we haterial: 07 PVC (SS ARE: 03 MILL SLO From 210 ff From ft Fr	CASING JOINTS: (Dia in. eight 3 lbs. DT t. to 270 ft. t. to 170 ft. t	GLUED to ft. /ft. Wall th From From From From From From	ft. to ft. to ft. to	in. to r gauge No ft. ft. ft.	ft.	How many 1	feet?

Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 06/14/91 under the business name of HENKLE DRILLING & SUPPLY by (signature) Dougla M. Wenkle

(Continued) WATER WELL RECORD Form WWC-5 KSA 82a-1212 :1 LOCATION OF WATER WELL: : Fraction : Township Number ; Section Number : Range Number COUNTY: 029 FORD ! NW 1/4 NW 1/4 NW 1/4 ; 31 ; T 27 ! R 23 2 WATER WELL OWNER: ALAN STEELE RR#, St. Address, Box # : Board of Agriculture, Division of Water Resources 67842-City, State, ZIP code : FORD, KS Application Number: TO : FROM : LITHOLOGIC LOG 164 : 180 : 07 FINE SAND 08 MEDIUM SAND 09 COARSE SAND 180 : 217 ; O7 FINE SAND OB MEDIUM SAND 28 ROCK 217 : 224 : 01 CLAY 224 : 268 : 07 FINE SAND 08 HEDIUM SAND 28 ROCK 268 : 280 : 19 SHALE

17 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 04/19/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 06/14/91 under the business name of HENKLE DRILLING & SUPPLY

Jouglan B. Henble by (signature) 9