

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number												
COUNTY: FORBES		NW 1/4 NW 1/4 SW 1/4	3	T 27 S	R 24 E W												
Distance and direction from nearest town or city street address of well if located within city? WILROADS GARDEN, KS 67801-																	
2 WATER WELL OWNER:		REYNOLDS, ROGER															
RR#, St. Address, Box # :		board of Agriculture, Division of Water Resources															
City, State, ZIP code :		WILROADS GARDEN, KS 67801- Application Number:															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 161 ELEVATION: 0															
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:5%; text-align: center;">1</td> <td style="width:10%; text-align: center;">NW</td> <td style="width:10%; text-align: center;">NE</td> <td style="width:10%; text-align: center;">SE</td> <td style="width:10%; text-align: center;">SW</td> <td style="width:10%; text-align: center;">E</td> </tr> <tr> <td style="text-align: center;">X</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>		1	NW	NE	SE	SW	E	X						Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.			
		1	NW	NE	SE	SW	E										
		X															
		WELL'S STATIC WATER LEVEL 55 ft. below land surface measured on mo/day/yr 08/29/95															
		Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm															
Estimated Yield 60 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm																	
		Bore Hole Diameter 9 in. to 161 ft., and in. to 0 ft.															
		WELL WATER TO BE USED AS: DOMESTIC															
		Was a chemical/bacteriological sample submitted to department? No :															
		If yes, mo/day/yr sample was submitted Water well disinfected? Yes															
5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED																	
Blank casing diameter 5 in. to 161 ft., Dia in. to 0 ft., Dia in. to 0 ft.																	
Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21																	
TYPE OF SCREEN OR PERFORATION MATERIAL: PVC																	
SCREEN OR PERFORATION OPENINGS ARE: SAW CUT																	
SCREEN PERFORATED INTERVALS:																	
From 136 ft. to 156 ft., From 0 ft. to 0 ft.																	
From 0 ft. to 0 ft., From 0 ft. to 0 ft.																	
GRAVEL PACK INTERVALS:																	
From 40 ft. to 161 ft., From 0 ft. to 0 ft.																	
From 0 ft. to 0 ft., From 0 ft. to 0 ft.																	
6 GROUT MATERIAL BENTONITE																	
Grout intervals: From 0 ft. to 40 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.																	
What is the nearest source of possible contamination: LIVESTOCK PENS																	
Direction from well? NORTH How many feet? 30																	
LITHOLOGIC LOG																	
FROM	TO	PLUGGING INTERVALS															
0	22	TOPSOIL SAND GRAVEL															
22	40	MEDIUM SAND CLAY LAYERS															
40	100	FINE SAND CALACHIE CLAY															
100	155	COARSE SAND GRAVEL															
155	161	YELLOW CLAY BLUE SHALE															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed under my jurisdiction and was completed on (mo/day/year) 08/31/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 09/21/95 under the business name of JOB'S WELL SERVICE, INC. by (signature) <i>Justin E. Cuit</i>																	