

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u>	<u>SW 1/4 SW 1/4 NE 1/4</u>	<u>1</u>	T <u>17</u> S	R <u>24</u> E <u>(W)</u>

Distance and direction from nearest town or city street address of well if located within city?

100 1/2 McCaustland Rd. #2

2 WATER WELL OWNER: <u>Chuck Taylor, Jr.</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>P.O. Box 1623</u>	Application Number:
City, State, ZIP Code: <u>Dodge City, KS 67801</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: ft. ELEVATION: ft.
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>38'</u> ft. below land surface measured on mo/day/yr <u>3-21-96</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>9 7/8</u> in. to <u>1 5/8</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>5</u> in. to <u>13 1/2</u> ft. Dia			11 Other (specify)
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR21</u>			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 None (open hole)
7 Torch cut			
SCREEN-PERFORATED INTERVALS:			
From <u>13 1/2</u> ft. to <u>15 1/2</u> ft.			
GRAVEL PACK INTERVALS:			
From <u>24</u> ft. to <u>89</u> ft.			
From <u>94</u> ft. to <u>155</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	4 Other
Grout Intervals: From <u>4</u> ft. to <u>24</u> ft.				
From <u>89</u> ft. to <u>94</u> ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
<u>3 Watertight sewer lines</u>	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage				
Direction from well? <u>West</u>				
How many feet? <u>30</u>				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Topsoil			
1	5	Brown clay			
5	21	Med. sand			
21	28	Brown clay			
28	34	Coarse sand			
34	40	Brown clay			
40	54	Med. sand			
54	66	Brown clay			
66	72	Brown sandy clay			
72	88	Med. sand			
88	94	Brown clay			
94	155	Med. sand - shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-21-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>533</u> This Water Well Record was completed on (mo/day/yr) <u>6-6-96</u> under the business name of <u>Jonathan Water Well Repair</u> by (signature) <u>[Signature]</u>
--