

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: FORD		SW 1/4 SW 1/4 SW 1/4	3	T 27 S	R 24 E/W
Distance and direction from nearest town or city street address of well if located within city? WILLAGOS GARDENS					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		DODGE CITY KS 67801			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 151 ft. ELEVATION: 15 ft.			
		Depth(s) Groundwater Encountered 1. 15 ft. 2. 60 ft. 3. 10-30-83 ft.			
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 10-30-83			
		Pump test data: Well water was 15 ft. after 2 hours pumping 50 gpm			
		Est. Yield 50 gpm: Well water was 15 ft. after 2 hours pumping 50 gpm			
		Bore Hole Diameter 8 in. to 151 ft., and 151 in. to 151 ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Observation well			
Was a chemical/bacteriological sample submitted to Department? Yes X No X		If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
② PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded			
Blank casing diameter 5 in. to 151 ft. Dia		in. to 151 ft. Dia			
Casing height above land surface 12" in. weight 29 lbs./ft. Wall thickness or gauge No. SDR 21					
TYPE OF SCREEN OR PERFORATION MATERIAL:		⑦ PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot ③ Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 131 ft. to 151 ft. From 151 ft. to 151 ft.			
GRAVEL PACK INTERVALS:		From 10 ft. to 151 ft. From 151 ft. to 151 ft.			
6 GROUT MATERIAL:		⑦ Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 151 ft.		From 151 ft. to 151 ft.			
What is the nearest source of possible contamination:		⑩ Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? WEST		How many feet? 100			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10	TOPSOIL			
10	60	SAND			
60	65	CLAY			
65	151	SAND + GRAVEL - SOME CLAY STRINGS			
151		SHALE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-30-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 217 This Water Well Record was completed on (mo/day/yr) 12-1-83					
under the business name of BRYN DRILLING CO INC by (signature) T. Thompson					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4