

1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County:	FORD	SW ¼ SW ¼ SE ¼	3	T 27 S	R 24 E/W

Distance and direction from nearest town or city street address of well if located within city?

Lot 11. Wilroads Garden School

2	WATER WELL OWNER:	USD #443- Wilroads Garden Elementary School	P.O. #201609
	RR#, St. Address, Box #	P.O. Box 460	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code	Dodge City, KS 67801	Application Number: 40,392

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION: Slope

Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr Sep. 28, 1991

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 140 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
9 Dewatering	12 Other (Specify below)	
XX Irrigation	4 Industrial	7 Lawn and garden only
10 Monitoring well		

Was a chemical/bacteriological sample submitted to Department? Yes No XX If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes XX No

TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued .XX . Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
XX ₂ PVC	4 ABS	7 Fiberglass		Threaded.
Blank casing diameter 5 in. to 100 ft., Dia	 in. to ft., Dia in. to ft.		
Casing height above land surface 18 in., weight 2.8 lbs./ft.		Wall thickness or gauge No. 265		
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	XX ₇ PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	XX ₈ Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 100 ft. to 140 ft., From ft. to ft.		
		From ft. to ft., From ft. to ft.		
GRAVEL PACK INTERVALS:		From 50 ft. to 140 ft., From ft. to ft.		
		From ft. to ft., From ft. to ft.		

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:		From 5 ft. to 50 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.
What is the nearest source of possible contamination:			10 Livestock pens		
XX Septic tank			14 Abandoned water well		
4 Lateral lines			11 Fuel storage		
7 Pit privy			15 Oil well/Gas well		
2 Sewer lines			12 Fertilizer storage		
5 Cess pool			16 Other (specify below)		
3 Watertight sewer lines			13 Insecticide storage		
6 Seepage pit				
9 Feedyard				
Direction from well? East			How many feet? 100		

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) October 1, 1991 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) October 2, 1991 under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

22-50017003