USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

× 1/4.

	[C	F		· · · ·		T	T		
1. Location of well:	County Fraction Lot 4		1	Section number		Township number	Range number		
	Ford	1/45 W 1/4 NW	1/4		4	т 27 s	R 24	E/W	
1 2 mi seet and 3/ govern Dadma City					er of well: Sam Caughron				
1.2 mi east and ¾ south Dodge City Street address of well location if in city:									
						Dodge City, Kansas			
4. Locate with "X" i	in section below:	Sketch map:				6. Bore hole dia.28 in	. Completion date 5=	5-76	
_ N	<u> </u>					Well depth 170 ft.			
1!						7 Cable tool Rotary Driven Dug			
X NW NE						Hollow rod Jetted Bored X Reverse rotary			
						8. Use: Domestic Pu	ıblic supply Indu	stry	
W 1 1 E						X Irrigation Air conditioning Stock			
						Lawn Oil field water Other			
						9. Casing: Material Meta Height: Above or below			
<u>t</u>						Threaded Welded X Surface 24 in. RMP PVC Weight 50 • 50 lbs./ft.			
S 1 M						Dig. 16 in. to 170 ft. dep	Weight	lbs./ft.	
				From	To	Dia in. to ft. dep	th large No 17	g or	
5. Type and color of	marer rai			From	10	10. Screen: Manufacturer's r			
Surface									
Coarse sand and gravel					1 2	Type Free-flo	_ Dia16		
Fine sand and clay mixed				.2	17	Slot/gauze 1/8 Set between 90	_ Length100		
Yellow clay with 35% fine sand mixed				1 2	20 46	ft. c	.ft. and <u>170</u>	ft.	
Fine to ½ med. sand with 10% clay mixed				20	46	Gravel pack? Yes Size ra		CMA	
1/2 med. sand and fine gravel				75	72	11. Static water level:	mo./d	day/yr.	
½ clay ½ sand				75	_	10 ft. below land sur	face Date <u>2-28</u>	- 76	
A-1 sand and gravel				106		12 Pymping level below Jano	surfaces: 27.00		
Gravel and sandy clay mixed				150		12 Pumping level below Jane	ors. pumping 2100 s	g.p.m.	
Silty blue clay with 25% sand				160	1 1	ft. after }	rs. pumpingg	g.p.m.	
½ sandrock & clay-½ gravel				164	. ,	13. Water sample submitted:		g.p.m. day/yr.	
Gray shale ://				170			Date	ady/yr.	
	Manager Manager and American Street Company	•		1 - 7 0		14. Well head completion:			
Strange for the . Wall	The state of the s	And a second of				Pitless adapter	X Inches above gr	ade	
Print to the State of the State	The same of the sa	er e		 		15. Well grouted? Yes			ţ/
						With: Neat cement Bentonite X Concrete			ີ ທີ
- m-	Manager & Angles					Depth: From ft. to .			
With the state of						16. Negrest source of possible ft	1894 Type sep	tic	tan
A statement of the stat						Well disinfected upon comple		No.	1
The state of the s						17. Pump:	X Not installed		_ <i>\</i>
		the same of the same of the same				manoracrorer s mane	lds		
						Model number 14JHO	_ HP <u>100</u> Volts		
						Length of drop pipe 140 Type:	_ ft. capacity 200 6)p.m.	(5
						Submersible	X Turbine		
		···				Jet	Reciproce	ating	
	(Use a second si	neet if needed)				Centrifugal	Other	3	<u> </u>
18. Elevation: 19. Remarks:						20. Water well contractor's o			
						This well was drilled under my	•	eport	Č
Topography:						is true to the best of my know Ace- Hi Inter		100	ر اړ
Hill						Business name		L90 ise No.	-13
Slope						Address Dodge Cit	y, Kansas		112
Upland						Signed Carl GO	1. ttl. 100.5	-26-	16
<u>X</u> Valley						Authorized rep	esentative		š٢