USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County	Fraction		number	Township number	mber Range number		
	Ford	Se 1/4 Se 1/4 Se 1/4	4	1	r 27 s	R 24w	E/W	
2. Distance and direction from necrest town or city: 5 mile East and 3. Owner of well: Henry Emitte 4 mile North on Wilroads Garden R.R. or street: RR# 3 Wilroads  Street address of well location if in city:								
from Dodge City, Kansas   City, state, zip code: Dodge City, Kansas 67801   4. Locate with "X" in section below: Sketch map:   6. Bore hole dia. 9 in. Completion date   28-76								
, N					Well depth 112ft.			
1     dawsE					7 Cable tool X Rotary Driven Dug			
NW   NE				ŀ	Hollow rod Jetted Bored Reverse rotary			
Apusé le will b					8. Use: X Domestic Public supply Industry Irrigation Air conditioning Stock			
sw se					9. Casing: Materia D 8 t. Height: Above or below			
S					Threaded Welded £1 Surface 2 in.  RMP _X _ PVC Weight 1 8 lbs./ft.  Dia in. tal ft. depth Wall Thickness: inches or			
1 Mile ————————————————————————————————————					Diain. to ft. dept	h Wall Thickness: inc	50	
5. Type and color of material				To	Diain. toft. depth gage No. 0 • 250			
Surface					Jess and Lov	well		
Dullace			1	1	Type RMP Dia. 5" Slot/gauze 1/16 Length 301t			
Silty clay			3	5	Set between 82 ft. and 112 ft.			
A-l medium to coarse sand and gravel			5	17	Gravel pack Size range of material 1 to 1			
Yellow dlay 20% fine sand and rock			17	30	11. Static water level:			
Fine to half medium sand and gravel				56	12. Pumping level below land surfaces:			
Half medium sand and gravel with clay				60	ft. after hrs. pumping g.p.m.			
layers					Estimated maximum yield		-g.p.m. /day/yr.	
Lay CLS				$\vdash$	•	Pate	rady/ yl .	
Fine to half medium sand with fine				70	14. Welf head completion: NC			
gravel				l	Pitless adapter 15. Well grouted? <u>Ves</u>	Inches above g	rade	
-Brown clay				06	With: X Neat cement	Bentonite C	oncrete \	
				86	Depth: From ft. to _			
Tine to half medium sand with fine				95 86-	16. Negreet source of possible ft Direction	Contemination SES	pic \	
gravel				95-	Well disinfected upon complet	rion? X Yes	No 15	
				112	17. Pump: Manufacturer's name	X Not installed		
R-1 10086 Coarse Builty and Braver			95		Model number	_ HP Volt		
					Length of drop pipe	ft. capacity ———	.g.p.m.   🥞	
					Type: Submersible	Turbine		
					Jet	Reciprod	cating S	
(Use a second sheet if needed)  18. Elevation: 19. Remarks:				-	Centrifugal	Other		
10. Elevation: 17. Netitaliks;				20. Water well contractor's certification:  This well was drilled under my jurisdiction and this report				
Topography:				is true to the best of my knowledge and belief.				
— Hill					Hodde Drilling Co. 302 No. Business name 1 Dodge City. Kansas 10			
Slope  X Upland					Address R#1 Dodge City, Kansa			
Valley					Signed Authorized representative Date 7-27			