

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County FORD	Fraction NE 1/4 NE 1/4 SW 1/4	Section number 11	Township number T 27 S R 24 E	Range number 24
2. Distance and direction from nearest town or city: Street address of well location if in city:		WILROADS GARDENS 3. Owner of well: John Smith R.R. or street: Rt 3 City, state, zip code: Dodge City KS 67801				
4. Locate with "X" in section below:		Sketch map:			6. Bore hole dia. 8 in. Completion date 11-15-79 Well depth 140 ft.	
					7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
5. Type and color of material		From	To	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 18 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight <input type="checkbox"/> lbs./ft. Dia. 5 in. to 140 depth Wall thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 250		
				10. Screen: Manufacturer's name PERLESS PVC Type PVC Dia. 5" Slot/gauze 1/16 Length 20' Set between 120 ft. and 140 ft. <input type="checkbox"/> ft. and <input type="checkbox"/> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/4"		
				11. Static water level: <input type="checkbox"/> mo./day/yr. 25 ft. below land surface Date 11-15-79		
				12. Pumping level below land surfaces: 25 ft. after 1 hrs. pumping 15 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield <input type="checkbox"/> g.p.m.		
				13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>		
				14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 18" Inches above grade		
				15. Well grouted? YES With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 25 ft.		
				16. Nearest source of possible contamination: ft. 100 Direction NE Type CORALS Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name GOULD Model number 1053 HP 3/4 Volts 230 Length of drop pipe 126 ft. capacity 15 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
		(Use a second sheet if needed)				
18. Elevation:		19. Remarks:		20. Water well contractor's certification:		
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley		OWNER AGREED TO INSTALL THE 4' X 4' X 4" REINFORCED CONCRETE PAD AROUND CASING		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BRAD BRLEY CO 217 Business name BUCKLIN KS License No. Address RW BRAY Signed RW BRAY Date 11-15-79 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5