WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County			Section number		lownship number	Kange number
1. Location of well:	Ford	NE 1/4 NE 1/4 SW	1/4	34	+	т 27 s	R 24 E/W
			3. Own	3. Owner of well: Dale Steele			
6 south & 4½ east of Dodge City R.R. or							
treet address of well	location if in city:		City, st	ate, zip	ode:Fo	rd, Kansas	
. Locate with "X" in	n section below:	Sketch map:				6. Bore hole dia. 28 in	. Completion date
N						Well depth 338 ft.	11-22-76
						7 Cable tool Rotary	Driven Dug
							Bored Reverse rotary
						8. Use: Domestic Public supply Industry X	
					:		
sw	SE					9. Casing: Material Met	
i x	1					Threaded WeldedX	_iSurfaceioin.
S						RMP PVC	Weight <u>51 • 55lbs./ft</u> .
1 Mile						Dia. 10 in. to 200 ft. dep	th Wall Thickness: inches or
. Type and color of r	material			From	То	Dia in. to ft. dep	
						Manufacturer's r	name
Surface				0	3	Type 17% Free-fl	
Fine sand				3	II	Slot/gauze 1/8	Length 240
Sandy brown clay				11	75	Set between <u>98</u>	ft. and 338 ft.
Fine sand with 15% clay mixed				75	95	ft. c	andft.
Good loose sand and gravel				95		Gravel pack? YesSize ra	nge of material 2 GOWN
Brown clay				130		4 T A	mo./day/yr.
1/2 med. sand and fine gravel				134	142	_NAft. below land sur	
3rown coleche clay				142	146	12 Pumping level below land 170 ft. after	surfaces: 1000
1/2 med. sand & fine gravel with small clay s			y st		167	170 ft. after 1	ors. pumping 1827 g.p.m.
Brown clay				' '	172	Estimated maximum yield	2500 g.p.m.
Good loose sand and gravel				172	196	13. Water sample submitted:	mo./day/yr.
Brown coleche clay				196			Date
½ med. to med. sand and gravel				207		14. Well head completion:	
Brown clay				217	224	Pitless adapter	X Inches above grade
Good loose sand and gravel				224		15. Well grouted? yes	
Brown clayo 67				255		With: Neat cement	BentoniteX Concrete
Good loose sand a nd gravel				257	277	Depth: From O ft. to	
Gray-clay-				277	281		
Cemented sand and gravel				.281		ft Direction	
Hard rock				287	288		1031103
Fine sand				288	291	17. Pump: Manufacturer's name	X Not installed
Sandy brown clay to a grant and a grant a grant and a				- 291	295	Manufacturer's name	HP Volts
1/2 med sand & fine grayel with clay mixed			d ,	2295	351	Length of drop pipe	ft. capacityg.p.m.
Gray shall	121,000	And the state of the property of the state o	17 24	351	375	Туре:	,
GIAN DHAI			exite	ma G		Submersible	Turbine
uray shar						Jet	Reciprocating
dray shar	41				l l		
	(Use a second sh	eet if needed)				Centrifugal	Other
	(Use a second sh	eet if needed)				20. Water well contractor's o	ertification:
		eet if needed)				20. Water well contractor's of This well was drilled under m	ertification: y jurisdiction and this report
8. Elevation:		seet if needed)				20. Water well contractor's of This well was drilled under my is true to the best of my know	ertification: y jurisdiction and this report ledge and belief.
		seet if needed)			-	20. Water well contractor's of This well was drilled under m	ertification: y jurisdiction and this report ledge and belief.
18. Elevation:		seet if needed)				20. Water well contractor's of This well was drilled under my is true to the best of my know Ace-Hi Intern	ertification: y jurisdiction and this report ledge and belief. ational 190
8. Elevation:		eet if needed)			-	20. Water well contractor's of This well was drilled under my is true to the best of my know Ace-Hi Intern. Business name	ertification: y jurisdiction and this report ledge and belief. ational 190 License No.