

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:

Section-Township-Range: 10-27-24EFraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): NW NW SE

County:

Ford

Location changed to:

10-27-24WNW NW SE

Other changes: Initial statements: _____

Changed to: _____

Comments:

E changed to W

verification method:

County maps, location and address information

initials:

MS

date:

3-3-06

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: FORD NW 1/4 NW 1/4 SE 1/4 10 T 27 S R 24 E

Distance and direction from nearest town or city street address of well if located within city?

WILROADS GARDEN, KS 67801-

2 WATER WELL OWNER: MURILLO, ANITA
 RR#, St. Address, Box #: ROUTE #3 -- BOX 218 Board of Agriculture, Division of Water Resources
 City, State, ZIP code: WILROADS GARDEN, KS 67801- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 155 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr 08/16/05
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm

Estimated Yield 70 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm

Bore Hole Diameter 10 in. to 155 ft., and in. to 0 ft.

WELL WATER TO BE USED AS: DOMESTIC

Was a chemical/bacteriological sample submitted to department? No;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED
 Blank casing diameter 5 in. to 155 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 110 ft. to 150 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 47 ft., From 0 ft. to 0 ft.
 From 58 ft. to 155 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE
 Grout intervals: From 5 ft. to 25 ft., From 47 ft. to 58 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: NONE
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	30	01 TOPSOIL 05 CLAY 37 FIN-COAR SAN			
30	40	14 WHITE CLAY			
40	60	14 WHITE CLAY 32 TAN CLAY			
60	80	32 TAN CLAY 10 FINE-MEDSAND			
80	100	32 TAN CLAY 10 FINE-MEDSAND 19 LAYERS			
100	150	37 FIN-COAR SAN 38 SMAL-MED GRA			
150	160	05 CLAY 07 BLUE SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/17/05 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 08/24/05
 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Joe's Well Service*