

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: FORD		NW 1/4 NW 1/4 SW 1/4	9	T 27 S	R 24 EW
Distance and direction from nearest town or city street address of well if located within city? 1 mi East of Dodge City on Hwy 154.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #		Application Number:			
City, State, ZIP Code		Dodge City, KS 67801			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 25.0 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 10.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16.10 ft. below land surface measured on mo/day/yr 12/17/97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 2 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 12 in. to 25 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel		5 Wrought iron			
3 RMP (SR)		6 Asbestos-Cement			
2 PVC		7 Fiberglass			
4 ABS		9 Other (specify below)			
		Threaded. Flush			
Blank casing diameter 4 in. to 25 ft. Dia		in. to ft. Dia			
Casing height above land surface 46 in., weight		lbs./ft. Wall thickness or gauge No. Schedule 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel		10 Asbestos-cement			
3 Stainless steel		8 RMP (SR)			
2 Brass		11 Other (specify)			
4 Galvanized steel		12 None used (open hole)			
6 Concrete tile		9 ABS			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		8 Saw cut			
3 Mill slot		11 None (open hole)			
2 Louvered shutter		6 Wire wrapped			
4 Key punched		9 Drilled holes			
		7 Torch cut			
		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 24.3 ft. to 15 ft. From ft. to ft.			
		From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 25.0 ft. to 9 ft. From ft. to ft.			
		From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement			
		2 Cement grout			
		3 Bentonite			
		4 Other			
Grout Intervals: From 6.0 ft. to 2.5 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		14 Abandoned water well			
4 Lateral lines		11 Fuel storage			
2 Sewer lines		15 Oil well/Gas well			
5 Cess pool		12 Fertilizer storage			
3 Watertight sewer lines		16 Other (specify below)			
6 Seepage pit		13 Insecticide storage			
9 Feedyard					
Direction from well? North & NorthEast		How many feet? 2400 ± 1000			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Soft w/ sd			
3	8	SD - med to fine			
8	15	SD - fine to crs			
15	23	SD - med to crs			
23	25	Clay w/ sd			
		ML			
		SM			
		SW			
		SW			
		CL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-2-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 581 This Water Well Record was completed on (mo/day/yr) 1-8-98 under the business name of Layne Western Co. by (signature) Steve Mitchell					