

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: FORD		NE ¼ NE ¼ NW ¼	16	T 27 S	R 24 E (W)
Distance and direction from nearest town or city street address of well if located within city? 1 mile east of Dodge City on Hwy 154					
2 WATER WELL OWNER: Excel Corporation, P.O. Box 1060 Hwy 154 East		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: Dodge City, KS 67801		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 85.3 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 22.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 72.37 ft. below land surface measured on mo/day/yr 12/1/97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 15-25 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 12 in. to 86.0 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)		Welded	
2 PVC 4 ABS		7 Fiberglass		Threaded Flashed	
Blank casing diameter 4 in. to 65.3 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 26.5 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 82.2 ft. to 65.8 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 85.3 ft. to 61.0 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 85.3 ft. to 2.0 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? North & North East		How many feet? 2 10,000			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	38	Sand - med to fine SP			
		Silt w/ SD @ 25'			
38	86	SD - fine to crs gravel SW			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-2-98 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 581		This Water Well Record was completed on (mo/day/yr) 1-8-98			
under the business name of Layne Western Co		by (signature) Steve Mitchell			