WATE	'R WF]	LL RECORD	Form WWC-5	Division of Water Resources App. No. 20120328		
		OF WATER WELL:	Fraction	Section Number Township No. Range Number		
1	nty: For		SE 1/4 SE 1/4 NW 1/4 SW 1/4		V	
				Global Positioning System (GPS) information:		
	from nearest town or intersection: If at owner's address, check here			Latitude: (in decimal degrees)	
3 3/4 South, 1/4 East of Dodge City			,	Longitude: (in decimal degrees		
5 5/4 Count, 1/4 Euck of Bodge Oily				Elevation:		
2 WATER WELLOWNER.				— Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27		
2 WATER WELL OWNER: BlueRidge Petroleum Corp. RR#, Street Address, Box #: P.O. Box 1913				Collection Method:		
C' Come 770 Colo				☐ GPS unit (Make/Model:		
Lity	, State, 2	Enid, Ol	k. 73702	Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m		
3 LOCATE WELL						
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 160 ft.					
SECTION BOX: Depth(s) Groundwater Encountered (1)						
N WELL'S STATIC WATER LEVEL115ft. below land surface measured on mo/day/yr. 6/28/12						
Pump test data: Well water wasft. after hours pumping g					ì	
EST. YIELD. N/Agpm. Well water wasft. after						
W Bore Hole Diameter 10 in. to .160 ft., and in. to						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
30	Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
1 1 1	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well					
	Was a chemical/bacteriological sample submitted to Department? Yes No					
S If yes, mo/day/yr sample was submitted						
Water went disinfected: 2 1 cs 140						
5 TYPE OF CASING USED: Steel V PVC Other						
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded						
Casing diameter .5 in. to .160 ft., Diameter in. to ft., Diameter in. to ft.						
				lbs./ft., Wall thickness or gauge No		
TYPE	TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From 160 ft. to 120 ft., From ft. to ft.						
	From ft. to ft., From ft. to ft.					
	GRAVEL PACK INTERVALS: From 160 ft. to20 ft., From ft. to ft.					
From						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: From						
What is the nearest source of possible contamination: Septic tank						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None						
Direction from well						
FROM	TO	LITHOLOG	IC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVAL	S	
	4	Top soil				
4	96	Tan clay				
96	123	Sand & gravel- med to				
123	136	Tan clay/ cemented sand				
136	149	Sand & gravel- med to large				
149	160	Dark gray shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, □ reconstructed, or □ plugged						
under my jurisdiction and was completed on (mo/day/year) .6/28/12 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) .7/5/12						
under the business name of Rosencrantz-Bemis by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						