

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u>	<u>NE 1/4 NE 1/4 SW 1/4</u>	<u>9</u>	T <u>27</u> S	R <u>25</u> EW

Distance and direction from nearest town or city street address of well if located within city?

From Dodge City, 1/2 mile south on 14th., 2 miles west, then 1/2 mile south

2 WATER WELL OWNER: <u>Steve Hale</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>814 Westlawn</u>	Application Number:
City, State, ZIP Code: <u>Dodge City, KS 67801</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>165'</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>79'</u> ft. below land surface measured on mo/day/yr <u>7-25-96</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>9 7/8"</u> in. to <u>165'</u> ft. and in. to ft. WELL WATER TO BE USED AS: ☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
☒ 2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>5"</u> in. to <u>145'</u> ft. Dia			11 Other (specify)
Casing height above land surface <u>12"</u> in. weight <u>200#</u> lbs./ft. Wall thickness or gauge No. <u>SOR 21</u>			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From <u>145'</u> ft. to <u>165'</u> ft.			
GRAVEL PACK INTERVALS:			
From <u>24'</u> ft. to <u>165'</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ 3 Bentonite	4 Other
Grout Intervals: From <u>4'</u> ft. to <u>24'</u> ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1</u>	<u>Topsoil</u>			
<u>1</u>	<u>20</u>	<u>Fine sand</u>			
<u>20</u>	<u>46</u>	<u>Fine sand + brown clay</u>			
<u>40</u>	<u>163</u>	<u>Med. - coarse sand</u>			
<u>163</u>		<u>Yellow clay, limestone, shale</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-25-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>533</u> This Water Well Record was completed on (mo/day/yr) <u>7-26-96</u> under the business name of <u>Jantzen Water Well Repair</u> by (signature) <u>[Signature]</u>
--