

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u>	<u>SE 1/4 SE 1/4 SE 1/4</u>	<u>2</u>	T <u>27</u> S	R <u>25</u> E (W)

Distance and direction from nearest town or city street address of well if located within city?

From Dodge City, 1/4 mile South on Hwy. 283

2 WATER WELL OWNER:	RR#, St. Address, Box #	Board of Agriculture, Division of Water Resources
<u>Boyd RV</u>	<u>1811 W. Wyatt Earp</u>	
City, State, ZIP Code	<u>Dodge City, KS. 67801</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	<u>165'</u>	<u>5-15-97</u>
	Depth(s) Groundwater Encountered	ft. 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL	<u>45</u> ft. below land surface measured on mo/day/yr
	Pump test data: Well water was	ft. after hours pumping gpm
	Est. Yield	gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter	<u>9 7/8</u> in. to <u>165</u> ft., and in. to ft.
	WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
	<u>1 Domestic</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>	If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <u>X</u> No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter	<u>5</u> in. to <u>145</u> ft., Dia		Threaded
Casing height above land surface	<u>12</u> in., weight	lbs./ft. Wall thickness or gauge No.	<u>SDR 21</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>1 PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	<u>8 Saw cut</u>	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>145</u> ft. to <u>165</u> ft.	From <u>128</u> ft. to <u>138</u> ft.	From <u>138</u> ft. to <u>165</u> ft.
GRAVEL PACK INTERVALS:	From <u>24</u> ft. to <u>128</u> ft.	From <u>138</u> ft. to <u>165</u> ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	4 Other
Grout Intervals:	From <u>4</u> ft. to <u>24</u> ft.	From <u>128</u> ft. to <u>138</u> ft.	From <u>138</u> ft. to <u>165</u> ft.	
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?	<u>Southwest</u>	How many feet?	<u>75</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>Sandy Topsoil</u>			
<u>2</u>	<u>49</u>	<u>Med. Sand</u>			
<u>49</u>	<u>54</u>	<u>Brown Clay</u>			
<u>54</u>	<u>65</u>	<u>Brown sandy clay</u>			
<u>65</u>	<u>97</u>	<u>Med. Sand & Sandstone ledges</u>			
<u>97</u>	<u>110</u>	<u>Brown Sandy clay</u>			
<u>110</u>	<u>135</u>	<u>Med. Sand</u>			
<u>135</u>	<u>138</u>	<u>Brown sandy clay</u>			
<u>138</u>	<u>165</u>	<u>Med. Sand</u>			
<u>165</u>		<u>limestone</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , <u>(2) reconstructed</u> , or <u>(3) plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>5-15-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>532</u> This Water Well Record was completed on (mo/day/yr) <u>6-13-97</u> under the business name of <u>Santean Water Well Repair</u> by (signature) <u>[Signature]</u>
