


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Ford County	Fraction 1/4 1/4 NW 1/4	Section number 10	Township number T 27 S. S	Range number R 25 E E/W
2. Distance and direction from nearest town or city: 1/4 Mile North, 1/4 East, 1/4 West, 1/4 South of JAG Concrete Dodge City, KS		Owner of well: Don Miller R.R. or street: RFD 1 City, state, zip code: Dodge City, Kansas 67801				
4. Locate with "X" in section below: 		Sketch map:		6. Bore hole dia. 26 in. Completion date 5-31-78 Well depth 160 ft.		
5. Type and color of material		From		To		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary
						8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
						9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 160 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth Gauge No. .219
						10. Screen: Manufacturer's name Johnson Type Johnson Galv. 100 - 16" Slot/gauze 0-100 Plain Length 100-110 Perf. Set between 110-120 Screen 120-130 Perf. 130-150 Screen 150-160 Perf. Gravel pack? yes Size range of material 1/4 to 5/8
						11. Static water level: <input type="checkbox"/> mo./day/yr. 60 ft. below land surface Date 4-7-78
						12. Pumping level below land surfaces: 88 ft. after 2 hrs. pumping 850 g.p.m. 103 ft. after 4 hrs. pumping 1300 g.p.m. Estimated maximum yield 1300 g.p.m.
						13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>
						14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. inches above grade
						15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No
				17. Pump: Manufacturer's name Could 6 stg. 12" Model number 910222 HP 100 Volts <input type="checkbox"/> Length of drop pipe 150 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drig. Co. 208 Business name License No. Address Box A, Garden City, KS Signed DeLoe Date 5-10-78 Authorized representative		

The
Professionals

MINTER-WILSON DRILLING CO.
INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 270 8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

**DON MILLER
FORD COUNTY**

**Location: NW 10-27-25 Approx. 1700 ft. west of house
and 1200 ft. south**

Static Water Level- 65'

Test #1

0	1	Top soil
1	30	Brown clay
30	124	Med. to coarse gravel (Loose)
124	131	Brown clay
131	140	Fine to med. sand and fine gravel (Loose)
140	151	Fine to med. sand and gravel with coarse white rock (Loose)
151	186	Brown sandy clay
186	190	Shale (Hard)

TD 160

100' Plain
10' Perf
10' Screen
10' Perf
20' Screen
10' Perf