

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Ford	Fraction SW 1/4 25' west center 1/4 1/4 1/4	Section number 16	Township number T 27 S	Range number R 25 E/W																											
2. Distance and direction from nearest town or city: 1-3/4 south-1 mi. west of Dodge City			3. Owner of well: Bell Farms																														
Street address of well location if in city:			R.R. or street: Dodge City, Kansas																														
4. Locate with "X" in section below:			City, state, zip code:																														
Sketch map: 			6. Bore hole dia. 28 in. Completion date 6-25-76 Well depth 191 ft.																														
5. Type and color of material <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr><td>Surface</td><td>0</td><td>3</td></tr> <tr><td>Brown clay</td><td>3</td><td>20</td></tr> <tr><td>Med. sand and fine gravel</td><td>20</td><td>32</td></tr> <tr><td>Fine sand</td><td>32</td><td>60</td></tr> <tr><td>Brown clay</td><td>60</td><td>74</td></tr> <tr><td>Med. sand and gravel</td><td>74</td><td>185</td></tr> <tr><td>Fine to half med. sand with 35% yellow clay</td><td>185</td><td>192</td></tr> <tr><td>Blue shale</td><td>192</td><td>195</td></tr> </tbody> </table>				From	To	Surface	0	3	Brown clay	3	20	Med. sand and fine gravel	20	32	Fine sand	32	60	Brown clay	60	74	Med. sand and gravel	74	185	Fine to half med. sand with 35% yellow clay	185	192	Blue shale	192	195	7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
				From	To																												
			Surface	0	3																												
			Brown clay	3	20																												
Med. sand and fine gravel	20	32																															
Fine sand	32	60																															
Brown clay	60	74																															
Med. sand and gravel	74	185																															
Fine to half med. sand with 35% yellow clay	185	192																															
Blue shale	192	195																															
8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																	
9. Casing: Material Metal Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 10 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 31.66 lbs./ft. Dia. 16 in. to 19 1/2 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 188																																	
(Use a second sheet if needed)			10. Screen: Manufacturer's name W.A. Brown Type 10% Free-flow Dia. 16 Slot/gauze 1/8 Length 120 Set between 71 ft. and 191 ft. Gravel pack? yes Size range of material 1/2 down																														
			11. Static water level: 110 ft. below land surface Date 5-24-76 mo./day/yr.																														
			12. Pumping level below land surfaces: 135 ft. after 1 hrs. pumping 1000 g.p.m. 155 ft. after 1 hrs. pumping 1200 g.p.m. Estimated maximum yield 1500 g.p.m.																														
			13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date 5-24-76 mo./day/yr.																														
14. Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> 10 inches above grade			15. Well grouted? Yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																														
			16. Nearest source of possible contamination: NA ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																														
			17. Pump: Goulds Not installed Manufacturer's name Goulds Model number 12JHMC HP 125 Volts 115 Length of drop pipe 180 ft. capacity 1050 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																														
			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Ace-Hi International 190 Business name Dodge City, Kansas License No. 190 Address Dodge City, Kansas Signed Carl G. Little Date 6-29-76 Authorized representative																														
18. Elevation:		19. Remarks:																															
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley																																	