


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:		County Ford	Township name Richland NWNE	Fraction ENE	Section number 25	Town number 27	Range number 25 W
Distance and direction from nearest town or city: 4 mile South 1 East				3 Owner of well: Ken Lloyd			
Street address of well location if in city: Dodge City, Kans.				Address: Box 296 Dodge City, Kansas			
Locate with "X" in section below: N 		Sketch map:		4 Well depth: 162 ft. Date of completion 11-1-75 Well diameter 5 in.			
2		Type and color of material		From	To	5 <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
		Surface		0	3	6 Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input type="checkbox"/>	
		Sandy brown clay		3	70	7 Casing: Material plastic High: above/below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. Diam. 5 in. to 162 ft. depth Drive shoe? <input type="checkbox"/> Yes <input type="checkbox"/> No in. to ft. depth	
		Good sand and gravel medium		70	115	8 Screen: 30' Screen Manufacturer Superior Type 15% Dia. 5" Slot/gauze 1/16 Length 40 Set between 122 ft. and 162 ft. Fittings: Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material 3/8	
		A-1 sand and gravel fine to medium		115	160	9 Static water level: 80 ft. below land surface Date 11-1-75	
Fine sand with 15% clay		160	185	10 Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.			
Yellow clay and 25% mixed with sand		185	177	11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date			
Gray shale		177	180	12 Well head completion: <input checked="" type="checkbox"/> Pitless adapter 12 inches above grade			
				13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From 3 ft. to 13 ft.			
				14 Nearest source of possible contamination: no ft. Direction Type Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			
				15 Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			
16 Remarks: elevation Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Hodde Drilling Co. 302 Business name License No. Address Rt #1 Dodge City, KS. Signed Billie Hodde Date 11-18-75 Authorized representative			