


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ford 029	NW 1/4 NW 1/4 NW 1/4	3	T 27 S	R 26 EW

Distance and direction from nearest town or city street address of well if located within city?

3 South, 1 East of Howell, Kansas

2 WATER WELL OWNER:	Mr. Greg Underwood	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:	Box 1849	Application Number: ---
City, State, ZIP Code:	Dodge City, KS 67801	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 150 ft. ELEVATION: Hill
	Depth(s) Groundwater Encountered: Not available ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: 8.1 ft. below land surface measured on mo/day/yr April 4, 1988
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield: 20 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 10 in. to 150 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
XX PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: 5 in. to 130 ft., Dia			Threaded
Casing height above land surface: 15 in., weight: 2.8 lbs./ft.			Wall thickness or gauge No. 265
TYPE OF SCREEN OR PERFORATION MATERIAL:	XX PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	XX Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 130 ft. to 150 ft.		
GRAVEL PACK INTERVALS:	From 70 ft. to 150 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	XXX Other Baroid Hole Plug
Grout Intervals:	From 0 ft. to 70 ft.			
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
XX Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? South			How many feet? 100	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	31	Clay			
31	60	Fine Sand			
60	74	Clay			
74	149	Large Gravel			
149	150	Black Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 4, 1988 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/yr) April 18, 1988
under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.