


1. Location of well: <div style="text-align: center; font-size: 1.2em; font-weight: bold;">Ford</div>		County <div style="text-align: center; font-size: 1.2em; font-weight: bold;">Center of SW 1/4</div>		Fraction <div style="text-align: center; font-size: 1.2em; font-weight: bold;">1/4 1/4 1/4</div>		Section number <div style="text-align: center; font-size: 1.2em; font-weight: bold;">9</div>		Township number <div style="text-align: center; font-size: 1.2em; font-weight: bold;">T 27 S</div>		Range number <div style="text-align: center; font-size: 1.2em; font-weight: bold;">R 26 E</div>	
2. Distance and direction from nearest town or city: 7W on Hwy. 56, 1 1/2 N, 1/4 E of Dodge City Street address of well location if in city:						3. Owner of well: Vernon Goetz R.R. or street: 2519 Hart Street City, state, zip code: Dodge City, KS 67801					
4. Locate with "X" in section below: <div style="text-align: center; margin-top: 10px;"></div>						Sketch map:					
5. Type and color of material						From		To		6. Bore hole dia. 28 in. Completion date 2-3-77 Well depth 145 ft.	
Surface						0		2		7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored <input checked="" type="checkbox"/> Reverse rotary	
Fine, Silty Sand						2		26		8. Use: Domestic Public supply Industry <input checked="" type="checkbox"/> Irrigation Air conditioning Stock Lawn Oil field water Other	
Clay						26		29		9. Casing: Material steel Height: Above or below Threaded Welded <input checked="" type="checkbox"/> Surface 12 in. RMP PVC Weight .188 lbs./ft. Dia. 16 in. to 80 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. .188	
Silty Sand						29		49		10. Screen: Manufacturer's name W. A. Brown & Johnson Type Johnson Dia. 16 Slot/gauze 40% Length 20 Set between 125 ft. and 145 ft. 17% 80 ft. and 125 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/4 to	
Clay						49		51		11. Static water level: mo./day/yr. 67 ft. below land surface Date 2-3-77	
Clay & Caliche						51		57		12. Pumping level below land surfaces: 145 ft. after 5 hrs. pumping 550 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.	
Sand & Gravel						57		83		13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No Date	
Clay & Caliche						83		113		14. Well head completion: Pitless adapter 12 Inches above grade	
Medium Sand - Some Clay Layers						113		121		15. Well grouted? With: Neat cement <input checked="" type="checkbox"/> Bentonite Concrete Depth: From 0 ft. to 10 ft.	
Medium Sand						121		136		16. Nearest source of possible contamination: ft. 170 mi. Direction West Type creek	
Medium Fine Sand						136		142		Well disinfected upon completion? Yes No	
Hard Layers & Clay						142		145		17. Pump: Not installed Manufacturer's name Simmons Model number S1100 HP 166 Volts Length of drop pipe 143 ft. capacity 550 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet Reciprocating <input type="checkbox"/> Centrifugal Other	
Shale						145				18. Elevation:	
(Use a second sheet if needed)										19. Remarks:	
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Woofert Drilling, Inc. 343 Business name License No. Address Hwy. 56, Dodge City, KS Signed [Signature] Date 9/67 Authorized representative					