			WATE	R WELL RECORD	Form WWC-5	KSA 82	a-1212		
1 LOCATION (R WELL:	Fraction		Sec	tion Number		ber	Range Number
	Ford	72	SE 1/4	SE 1/4	NE 1/4	16	т 27	s	R 26 E₩
			•	ddress of well if locat					
				l mile East	and $\frac{1}{2}$ mil	e South			
 √		R: Rick S							
		: Happy					Board of Agri	culture, Di	vision of Water Resources
City, State, ZIP Code : Dodge City, Kansas 67801 Application									
3 LOCATE WE	ELL'S LOC	ATION WITH 4	DEPTH OF C	OMPLETED WELL	400	. ft. ELEVA	ATION:		
⊢ AN "X" IN S	ECTION E								
1		·	VELL'S STATIC	WATER LEVEL	L39 ft. b	elow land su	rface measured on m	o/day/yr	June. 15 , . 1.986
	w I-	- NE	Pump	test data: Well wa	ter wasl	47 ft. a	after6 h	ours pum	ping 40 gpm
\	w -	- NE E	st. Yield 🤄	0. gpm: Well wa	ter was	ft. a	after h	ours pum	ping gpm
•	<u>i</u>	X] . [B	Bore Hole Diame	ter	 . 400	ft.,	and	in. 1	o
		· · ·	VELL WATER T	O BE USED AS:	5 Public wate	r supply	8 Air conditioning	11 ln	jection well
lī L,	l	- SE	1 Domestic	3 Feedlot	6 Oil field wat	ter supply	9 Dewatering	12 O	ther (Specify below)
'	<u>" -</u>	- 35	2 Irrigation	4 Industrial	7 Lawn and g	arden only	10 Observation well		
	i	_ ı v	Vas a chemical/t	acteriological sample	submitted to De	partment? Y	esNoXXX	; If yes, n	no/day/yr sample was sub-
1	S	n	nitted			Wa	ater Well Disinfected?	Yes	xxx No
5 TYPE OF B	LANK CAS	SING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOINT	S: Glued	XXClamped
1 Steel		3 RMP (SR)		6 Asbestos-Cement					[
2 PVC		4_ABS		7 Fiberglass				Thread	ed
									. to ft.
Casing height a	above land	surface	2	.in., weight	200.psi	Ibs.	/ft. Wall thickness or	gauge No.	.SDR. 21
TYPE OF SCR	EEN OR I	PERFORATION	MATERIAL:		7 PV		10 Asbes	tos-cemen	
1 Steel		3 Stainless s	steel	5 Fiberglass		P (SR)	11 Other	(specify) .	
2 Brass		4 Galvanized	d steel	6 Concrete tile	9 AB	S	12 None	used (oper	n hole)
SCREEN OR F	PERFORA	TION OPENING	S ARE:	5 Gau	zed wrapped		8 Saw cut	•	11 None (open hole)
1 Continu	ous slot	3 Mill	slot	6 Wire	wrapped		9 Drilled holes		
2 Louvere	ed shutter	4 Key	punched	7 Toro			, , , , , , , , , , , , , , , , , , , ,		
SCREEN-PERF	FORATED	INTERVALS:							ft.
GRAV	VEL PACK	INTERVALS:	From 2	.Q ft. to .	4.0.0	ft., Fro	om		
			From	ft. to		ft., Fro	om	ft. to	ft.
6 GROUT MA		1 Neat ce		2 Cement grout					
Grout Intervals:					ft.	to	ft., From		ft. to _. ft.
		ce of possible co					stock pens		andoned water well
1 Septic t	tank	4 Lateral		7 Pit privy			storage		well/Gas well
2 Sewer		5 Cess p		8 Sewage la	goon		lizer storage	16 Oth	er (specify below)
	•	lines 6 Seepaç	ge pit	9 Feedyard			cticide storage		
Direction from							any feet?	FI 101 0016	1100
	TO 15	rop soil °	LITHOLOGIC	LUG	FROM	то	LI	<u> THOLOGIC</u>	LUG
		Top soil &	стау						
		Clay Clay & fin	e sand						
		Clay & fin	e sanu						
		Fine sand	dium aa						
		Fine to me		. 4					
		Medium to		ıu			-		
		Clay & roc							
		Brown clay		h-1-					
		Rock layer		nale					
		Blue shale		. .					
		Blue shal		tone	-				
		Sand stone			-				
		Sand stone	•						
		sand stone	& clay (4	ft.)					
		Sandstone				L			
7 CONTRACT	TOR'S OR	LANDOWNER'S	S CERTIFICATI	ON: This water well	was (1) constru	cted, (2) rec	onstructed, or (3) plug	gged unde	r my jurisdiction and was
									vledge and belief. Kansas
Water Well Co	ntractor's 1	icense No	. 1.7.9	This Water	Well Record wa		on (mo/day/yr) . J.u.		.1.986
				e, Inc. Cima			ature) Tauy		k.
									top three copies to Kansas
		and retain one for		инопиненкан Geology, Не	guiation and Permit	ung secuon, I	upera, nansas 00020-750	o, relepnon	e: 913-862-9360. Send one