

1 LOCATION OF WATER WELL:		Fraction		Form WWC-5		KSA 82a-1212	
County: Ford		NW 1/4 NW 1/4 SW 1/4		Section Number 17		Township Number T 27 S	
Range Number R 26		E 1/4					
Distance and direction from nearest town or city street address of well if located within city?							
7 1/2 West, 2 1/2 South of Dodge City, Kansas							
2 WATER WELL OWNER:		David Buchanan					
RR#, St. Address, Box # :		1705 11th Avenue					
City, State, ZIP Code :		Dodge City, Kansas 67801					
Board of Agriculture, Division of Water Resources		Application Number: ---					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 200 ft. ELEVATION: Slope					
N		Depth(s) Groundwater Encountered Not available ft. 2 ft. 3 ft.					
WELL'S STATIC WATER LEVEL: 136 ft. below land surface measured on mo/day/yr September 7, 1989		Pump test data: Well water was ft. after hours pumping gpm					
Est. Yield 20 gpm: Well water was ft. after hours pumping gpm		Bore Hole Diameter 10 in. to 200 ft. and in. to ft.					
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well					
XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No XX		If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes XX No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded		XX PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 160 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface 18 in. weight 2.8 lbs./ft. Wall thickness or gauge No. 265					
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped XX Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 160 ft. to 200 ft. From ft. to ft.					
GRAVEL PACK INTERVALS:		From 20 ft. to 200 ft. From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite XX Other Baroid Hole Plug					
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
XX Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? East		How many feet? 100					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 2 Topsoil							
3 60 Clay							
60 120 Caliche							
120 140 Med. to Lar. Sand							
141 161 Clay							
162 191 Med. to Lar. Sand & Gravel							
191 200 Caliche							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) September 11, 1989 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) September 25, 1989 under the business name of FRIESEN WINDMILL & SUPPLY, INCORPORATED by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.							