

1 LOCATION OF WATER WELL: COUNTY: FORD		Fraction NW 1/4 NW 1/4 NW 1/4	Section Number 25	Township Number T 27 S	Range Number R 26 E																																																												
Distance and direction from nearest town or city street address of well if located within city? 3 MILES EAST OF HOWELL ON HIGHWAY 50 (NORTH SIDE OF ROAD)																																																																	
2 WATER WELL OWNER: RR#, St. Address, Box #: R.F.D. #2 City, State, ZIP code : DODGE CITY, KS 67801-		FOX, J. W. Board of Agriculture, Division of Water Resources Application Number:																																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 225 ELEVATION: 0 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.																																																															
<table border="1" style="width:100%; text-align: center;"> <tr> <td colspan="2">X</td> <td colspan="2"></td> </tr> <tr> <td>NW</td> <td>NE</td> <td colspan="2"></td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> </tr> <tr> <td>SW</td> <td>SE</td> <td colspan="2"></td> </tr> </table>		X				NW	NE							SW	SE			WELL'S STATIC WATER LEVEL 54 ft. below land surface measured on mo/day/yr 05/27/93 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm Estimated Yield 80 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm Bore Hole Diameter 8 in. to 225 ft., and in. to 0 ft. WELL WATER TO BE USED AS: DOMESTIC Was a chemical/bacteriological sample submitted to department? No ; If yes, mo/day/yr sample was submitted Water well disinfected? Yes																																															
X																																																																	
NW	NE																																																																
SW	SE																																																																
5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED Blank casing diameter 5 in. to 225 ft., Dia in. to 0 ft., Dia in. to 0 ft. Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC SCREEN OR PERFORATION OPENINGS ARE: SAW CUT																																																																	
SCREEN PERFORATED INTERVALS: From 200 ft. to 220 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 40 ft. to 225 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft.																																																																	
6 GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. to 40 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. What is the nearest source of possible contamination: NONE - NEW SITE Direction from well? How many feet? 0																																																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>20</td> <td>TOPSOIL SAND ROCK LAYERS</td> <td></td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>40</td> <td>MED-COARSE SAND SAND CLAY</td> <td></td> <td></td> <td></td> </tr> <tr> <td>40</td> <td>60</td> <td>CLAY</td> <td></td> <td></td> <td></td> </tr> <tr> <td>60</td> <td>80</td> <td>CLAY FINE - MED SAND IN LAYERS</td> <td></td> <td></td> <td></td> </tr> <tr> <td>80</td> <td>100</td> <td>CLAY MEDIUM SAND IN LAYERS</td> <td></td> <td></td> <td></td> </tr> <tr> <td>100</td> <td>160</td> <td>MED-COARSE SAND GRAVEL VERY LOOSE</td> <td></td> <td></td> <td></td> </tr> <tr> <td>160</td> <td>222</td> <td>MED-COARSE SAND GRAVEL SAND</td> <td></td> <td></td> <td></td> </tr> <tr> <td>222</td> <td>226</td> <td>CLAY BLUE SHALE</td> <td></td> <td></td> <td></td> </tr> <tr> <td>226</td> <td>240</td> <td>BLUE SHALE</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	20	TOPSOIL SAND ROCK LAYERS				20	40	MED-COARSE SAND SAND CLAY				40	60	CLAY				60	80	CLAY FINE - MED SAND IN LAYERS				80	100	CLAY MEDIUM SAND IN LAYERS				100	160	MED-COARSE SAND GRAVEL VERY LOOSE				160	222	MED-COARSE SAND GRAVEL SAND				222	226	CLAY BLUE SHALE				226	240	BLUE SHALE			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																												
0	20	TOPSOIL SAND ROCK LAYERS																																																															
20	40	MED-COARSE SAND SAND CLAY																																																															
40	60	CLAY																																																															
60	80	CLAY FINE - MED SAND IN LAYERS																																																															
80	100	CLAY MEDIUM SAND IN LAYERS																																																															
100	160	MED-COARSE SAND GRAVEL VERY LOOSE																																																															
160	222	MED-COARSE SAND GRAVEL SAND																																																															
222	226	CLAY BLUE SHALE																																																															
226	240	BLUE SHALE																																																															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 05/28/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 06/19/93 under the business name of JOE'S WELL SERVICE, INC. by (signature) <i>Joe's Well Service</i>																																																																	