WATER WELL RECO	RD	Form W	WC-5	Division of Wate	r Resources App. No	20,059
1 LOCATION OF WATE		Fraction		Section Number	Township No.	Range Number
County: FORD		1/4 NE 1/4 NE		4	T 27 S	R 26 □E ▼W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here				Global Positioning System (GPS) information:  Latitude:		
W SIDE OF DODGE CITY ON HWY 56 - 1-1/3RDS M SW, 5 M W,				Longitude: (in decimal degrees)		
5,083 FT. NORTH & 652 FT. WEST				Elevation:		
2 WATER WELL OWNER: STAN GOETZ				Collection Method:		
RR#, Street Address, Box #: 10950 101 ROAD City, State, ZIP Code : DODGE CITY KANSAS 67801				GPS unit (Make/Model:)		
City, State, ZIP Code : DODGE CITY, KANSAS 67801				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m		
3 LOCATE WELL						
WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL						
WELL'S STATIC WATER LEVEL124ft. below land surface measured on mo/day/yr10-1-12						
Pump test data: Well water wasft. after hours pumping gpm						
W - NW - NE - EST. YIELD						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
S If yes, mo/day/yr sample was submitted						
mile  Water well disinfected? ☐ Yes ☑ No						
5 TYPE OF CASING USED:  Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter16 in. to140 ft., Diameter in. to ft., Diameter ft., Diameter ft., Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
Brass Galvanized Steel None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
☐ Louvered shutter ☐ Key punched ☑ Wire wrapped ☐ Saw cut ☐ Other (specify)						
From						
GRAVEL PACK INTERVALS: From						
From						
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft. ft. o ft. ft.						
What is the nearest source of possible contamination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well						
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well						
Direction from well	LITHOLOG					ICCNIC INTERVALE
TROW TO	LITTOLOC	iic Lod	FROM	TO LITHO, L	OG (cont.) of FLC	JGGING INTERVALS
SEE ATT	ACHED LOG					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year) .10-1-12 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year) .10-11-12						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly, Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						

## TER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic and Repairing

INCORPORATED

Phone 620-276-8269 GARDEN CITY, KANSAS 67846

NAME

STAN GOETZ - CIRCLE # 48

COUNTY

FORD

DATE

6-7-12

LOCATION:

NE 1/4 4-27- 26 - SOUTH OF HOWELL TO BEESON ROAD - 1 MILE EAST

ON THE SOUTH SIDE

- NORTHEAST EDGE OF CIRCLE

STATIC WATER LEVEL -

## TEST#1

1' - TOP SOIL 0' TO .

1' TO 10' - BROWN CLAY

10' TO 15' - FINE TO MEDIUM SAND

15' TO 55' - BROWN SANDY CLAY

55' TO 163' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH STRIPS OF BROWN SANDY CLAY

163' TO 170' - SHALE - 250 PULL DOWN