


1 LOCATION OF WATER WELL:	Fraction County: GRAY SE $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 12	Township Number T 27 S	Range Number R 27 EW
---------------------------	--	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

6 1/2 MILE SOUTH CIMARRON HWY 23 1/4 M. EAST

2 WATER WELL OWNER:	CURT ENZ	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	CIMARRON, KS.	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL ft. ELEVATION:
--	--



Depth(s) Groundwater Encountered 118 ft. 2. ft. 3. ft. 10/17/87

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 9.7/8 in. to 210 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

X1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) STOCK WELL

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
------------------------------	----------------	-----------------	--

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

X PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 183 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 20 in., weight 200 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 5 Mill slot 6 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 7 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 173 ft. to 193 ft., From ft. to ft.

From 203 ft. to 208 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 50 ft. to 208 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 4 ft. to 30 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well?

FROM	TO	LITHOLOGIC LOG	FROM	TO	CENTER OF FIELD PLUGGING INTERVALS
0	10	TOP SOIL			
10	41	BROWN SANDY CLAY			
41	60	FINE SAND			
60	80	BROWN SANDY CLAY			
80	87	FINE TO MED SAND AND GRAVEL			
87	91	BROWN SANDY CLAY			
91	144	FINE TO MED SAND AND GRAVEL			
144	160	BROWN SANDY CLAY			
160	186	FINE TO MED SAND AND GRAVEL			
186	193	BROWN STICKY CLAY			
193	204	FINE TO MED SAND AND GRAVEL			
204	253	BROWN AND GRAY CLAY			
253					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/25/87 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 172 This Water Well Record was completed on (mo/day/yr) 6/88

under the business name of JONAGAN DRILLING CO.

by (signature) 