


1 LOCATION OF WATER WELL		Fraction NW $\frac{1}{4}$ NE $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$			Section Number 18	Township Number T 27 S	Range Number R 27 E/W								
Distance and direction from nearest town or city? 8 miles South & 11 miles East, 3/4 miles North of Cimarron, Kansas				Street address of well if located within city?											
2 WATER WELL OWNER: Dale Eichensauer (Henter)				Board of Agriculture, Division of Water Resources Application Number:											
RR#, St. Address, Box # : City, State, ZIP Code : Ingalls, Kansas 67853															
3 DEPTH OF COMPLETED WELL 204 ft. Bore Hole Diameter 8 in. to 204 ft., and in. to ft.															
Well Water to be used as: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Stock well															
Well's static water level 98 ft. below land surface measured on June month 18 day 1979 year															
Pump Test Data : Well water was ft. after hours pumping. gpm Est. Yield 20 gpm: Well water was ft. after hours pumping. gpm															
4 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued <input checked="" type="checkbox"/> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing dia 5 in. to 204 ft., Dia in. to ft., Dia in. to ft.															
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 200 Jet Stream															
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)															
Screen or Perforation Openings Are: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)															
Screen-Perforation Dia 1/8 in. to 20 ft., Dia in. to ft., Dia in. to ft.															
Screen-Perforated Intervals: From 180 ft. to 200 ft., From ft. to ft. From ft. to ft., From ft. to ft.															
Gravel Pack Intervals: From 10 ft. to 204 ft., From ft. to ft., From ft. to ft.															
5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.															
What is the nearest source of possible contamination: none - in pasture 1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well 3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)															
Direction from well How many feet ? Water Well Disinfected? Yes <input checked="" type="checkbox"/> No Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, date sample was submitted month day year: Pump Installed? Yes No <input checked="" type="checkbox"/> Windmill															
If Yes: Pump Manufacturer's name Model No. HP Volts Depth of Pump Intake ft. Pumps Capacity rated at gal/min.															
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other															
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) <u>plugged</u> under my jurisdiction and was completed on July month 2nd day 1979 year															
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179															
This Water Well Record was completed on August month 22nd day 1979 year under the business name of <u>JOHN'S WELL SERVICE - CIMARRON, KS.</u> by (signature) <u>John Creek</u>															
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 				FROM 0 15 75 90 105 120 120 165 165 195 195 210 210 220		TO 15 75 90 105 120 165 195 210 220		LITHOLOGIC LOG Top soil & clay Clay Clay & fine sand Fine to medium sand Medium sand Medium to fine sand & clay layers Medium sand Medium to coarse sand Coarse sand, clay & blue shale		FROM 0 15 75 90 105 120 120 165 165 195 195 210 210 220		TO 15 75 90 105 120 165 195 210 220		LITHOLOGIC LOG	
ELEVATION:															
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)															
INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.															