


1 LOCATION OF WATER WELL: County: <i>Gray</i>	Fraction <i>SW 1/4 SW 1/4 SW 1/4</i>	Section Number <i>10</i>	Township Number <i>T 27 S</i>	Range Number <i>R 27 E/W</i>	
Distance and direction from nearest town or city street address of well if located within city? <i>From Ensign 3 1/2 miles north then 2 miles west</i>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Malinda Bryan P.O. Box 803 Cimarron, KS 67835				Board of Agriculture, Division of Water Resources Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <i>126 1/2'</i> ft. ELEVATION: <i>126 1/2'</i>				
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
WELL'S STATIC WATER LEVEL <i>127</i> ft. below land surface measured on mo/day/yr					
Pump test data: Well water was ft. after hours pumping gpm					
Est. Yield gpm: Well water was ft. after hours pumping gpm					
Bore Hole Diameter in. to ft. and in. to ft.					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>					
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below) <i>Gauze, tin</i>	CASING JOINTS: Glued <input type="checkbox"/> Clamped <input type="checkbox"/> Welded <input type="checkbox"/> Threaded <input type="checkbox"/>		
Blank casing diameter <i>5"</i> in. to ft., Dia in. to ft., Dia in. to ft.	lbs./ft. Wall thickness or gauge No.				
Casing height above land surface <i>36"</i> in., weight					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) <i>NA</i> 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) <i>NA</i>					
SCREEN-PERFORATED INTERVALS: From <i>NA</i> ft. to <i>NA</i> ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: Grout Intervals: From <i>3'</i> ft. to <i>126 1/2'</i> ft., From ft. to ft., From ft. to ft., From ft. to ft.	1 Neat cement 2 Cement grout 3 Bentonite	4 Other			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	
			<i>3</i>	<i>126 1/2'</i> <i>Bentonite chips</i>	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>3-17-95</i> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <i>533</i> This Water Well Record was completed on (mo/day/year) <i>4-7-95</i> under the business name of <i>Tancon Water Well Repair</i> by (signature) <i>Ed S. Gray</i>					