

## WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 12	Township Number T 27 S	Range Number R 28 E (W)
Distance and direction from nearest town or city street address of well if located within city? From Cimarron, Ks. - 5 miles South on highway 23 and 1/2 mile East					
2 WATER WELL OWNER:		Richard Strawn			
RR#, St. Address, Box #:		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code:		Cimarron, Kansas 67835 Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 185 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 86 ft. below land surface measured on mo/day/yr August 16, 1983 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 30 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 185 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well stock well Was a chemical/bacteriological sample submitted to Department? Yes No XXX If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XXX No			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 2 PVC	6 Asbestos-Cement 3 RMP (SR) 4 ABS	7 PVC 8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued XXX, Clamped Welded Threaded
Blank casing diameter		5 in. to 185 ft., Dia	12 in. to 200 psi lbs./ft. Wall thickness or gauge No.	SDR 21	
Casing height above land surface		10 Asbestos-cement			
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass 1 Steel 2 Brass	6 Concrete tile 3 Stainless steel 4 Galvanized steel	7 PVC 8 RMP (SR) 9 ABS	11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 1 Continuous slot 2 Louvered shutter	6 Wire wrapped 3 Mill slot 4 Key punched	7 Torch cut 8 Saw cut 9 Drilled holes	10 Other (specify) 11 None (open hole)
SCREEN-PERFORATED INTERVALS:		From 160 ft. to 180 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:		From 10 ft. to 185 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 0 ft. to 10 ft.	2 Cement grout From ft. to ft.	3 Bentonite From ft. to ft.	4 Other From ft. to ft.
What is the nearest source of possible contamination: none 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)					
Direction from well? FROM TO LITHOLOGIC LOG 0 15 Topsoil & fine sand 15 45 Fine sand 45 60 Fine sand & medium sand 60 75 Medium to coarse sand 75 105 Coarse sand 105 120 Coarse sand & clay (4 ft.) 120 135 Clay & fine to medium sand 135 150 Medium sand 150 165 Medium to coarse sand 165 195 Medium to coarse sand & clay 195 205 Clay & rock layers					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) August 16, 1983 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179. This Water Well Record was completed on (mo/day/yr) August 27, 1983 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) <i>Larry Creek</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					