

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County:	Gray	1/4	Near Center	1/4	22	T	27	R	28
			SW	1/4		S		E/W	

Distance and direction from nearest town or city street address of well if located within city?

From south side of Cimarron - $8\frac{1}{2}$ Miles south on Hwy 23, 1 Mile West, 1335 ft. North & 3860 ft.

2] WATER WELL OWNER:	Pete B.J. Koehn	West
RR#, St. Address, Box # :	Route 2 - Box 11	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Cimarron, Ks. 67835	Application Number: 20,315 & 33,082

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W E

N S

SW NW NE SE

4 DEPTH OF COMPLETED WELL: 240 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 122 ft. below land surface measured on mo/day/yr 3-25-91

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 30 in. to 240 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No XX

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	XX
Blank casing diameter			7 Fiberglass	145 to 150	230 to 240
Casing height above land surface			Threaded		
TYPE OF SCREEN OR PERFORATION MATERIAL:			20" - 52.73		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS			20" From	135	ft. to
			From	220	ft. to
GRAVEL PACK INTERVALS:			From	25	ft. to
			From	70	ft. to

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 25 ft., From 70 ft. to 128 ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? SW How many feet? 100 ft west
15 ft south

Direction from well:		SW	How many feet:		15 ft south
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		see attached log			

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-25-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208. This Water Well Record was completed on (mo/day/yr) 4-22-91 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller