

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction SE $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 25	Township Number T 27 S	Range Number R 28 NW
---------------------------	--	----------------------	---------------------------	-------------------------


County: Gray

Distance and direction from nearest town or city street address of well if located within city?

4 $\frac{1}{2}$ North and 5 $\frac{1}{2}$ East of Montezuma, Kansas

2 WATER WELL OWNER:	Mr. Donnie Koehn	RR#, St. Address, Box # :	Rt. 2, Box 81	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Montezuma, Kansas 67867	Application Number:	--	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 248 ft. ELEVATION: Level
	Depth(s) Groundwater Encountered 1. 200 ft. 2. ft. 3. ft.



WELL'S STATIC WATER LEVEL 200 ft. below land surface measured on mo/day/yr Oct. 15, 1991

Pump test data: Well water was ft. after hours pumping gpm
Est. Yield 40 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 3/4 in. to 248 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	Welded
XX PVC	4 ABS	7 Fiberglass	Threaded

Blank casing diameter 5 in. to 208 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface 18 in. weight 2.8 lbs./ft. Wall thickness or gauge No. 265

TYPE OF SCREEN OR PERFORATION MATERIAL:	XX PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	11 Other (specify)
2 Brass	4 Galvanized steel	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	XX Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	12 Other (specify)
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)

SCREEN-PERFORATED INTERVALS:	From 208 ft. to 248 ft.	From ft. to ft.
	From ft. to ft.	From ft. to ft.

GRAVEL PACK INTERVALS:	From 20 ft. to 248 ft.	From ft. to ft.
	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	XX 3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 20 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well
xx 1 Septic tank	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	13 Insecticide storage	

Direction from well?	Northwest	How many feet?	100
----------------------	-----------	----------------	-----

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	18	Topsoil			
18	115	Sand			
115	180	Sandy White Clay			
180	248	Sand & Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) October 16, 1991 and this record is true to the best of my knowledge and belief. Kansas
--

Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) October 23, 1991 under the business name of Friesen Windmill & Supply Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

22-9001260304