


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Gray County	Fraction 1/4 NE 1/4 SW 1/4	Section number 31	Township number T 27 S. S	Range number R 28 E/W
2. Distance and direction from nearest town or city: 22 mile road 1 mile East 1/2 mile North 500 ft.		3. Owner of well: Carl Love		R.R. or street: Montezuma, Kansas 67867		
Street address of well location if in city: North East of Pivot		City, state, zip code:				
4. Locate with "X" in section below: 		Sketch map:		6. Bore hole dia. 26 in. Completion date 6-30-78 Well depth 190 ft.		
5. Type and color of material		From	To	7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				8. Use: Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia 16 in. to 190 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219		
				10. Screen: Manufacturer's name Johnson Type Johnson Galv. 100 16" Slot/gauze 120-155 Perfor Length <input type="checkbox"/> Set between 155-185 Screen ft. 185-190 Perfor ft. Gravel pack? yes Size range of material 1/4 to 5/8		
				11. Static water level: <input type="checkbox"/> mo./day/yr. 115 ft. below land surface Date 5-19-78		
				12. Pumping level below land surfaces: 139 ft. after 2 hrs. pumping 975 g.p.m. 151 ft. after 2 hrs. pumping 1375 g.p.m. Estimated maximum yield 1375 g.p.m.		
				13. Water sample submitted: <input type="checkbox"/> mo./day/yr. Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>		
				14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. inches above grade		
				15. Well grouted? yes With: Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete <input type="checkbox"/> Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Gould - 5 stage 12" Model number JLC HP 125 Volts <input type="checkbox"/> Length of drop pipe 180 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Reciprocating <input type="checkbox"/> Other		
				(Use a second sheet if needed)		
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Winter Wilson Drig. 208 Business name License No. Address Box A, Garden City, KS Signed Richard A. Wilson Date 6-9-78 Authorized representative			
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WW-5

The
Professionals

MINTER-WILSON DRILLING CO.
INCORPORATED

Drilling
and Completion
Contractors
and Engineers

Phone 275-8265 • P.O. Box A • GARDEN CITY, KANSAS 67841

CARL LOVE
GRAY COUNTY
4/24/78

Location: SW 31-27-28 south of Ingalls to 23 mile road
1 mile east, $\frac{1}{4}$ north 500ft. north east of
pivot or 200 ft. north of best test.

Static Water Level- 95'

Test #1

0	6	Top soil
6	22	Brown clay
22	32	Fine sand 20% clay
32	51	Brown clay
51	59	Fine sand
59	101,	Brown sandy clay
101	119	Fine to med. sand and gravel Loose
119	125	Brown sandy clay
125	133	Fine to med. sand and gravel 15% clay Tight
133	181	Fine to med. sand and gravel
181	195	Brown sandy clay mixed with rock Hard
195	240	Brown sandy clay
240	257	Yellow clay mixed with yellow rock No Good
257	260	Shale

TD 191