

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction NW $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 3	Township Number T 27 S	Range Number R 29 E/W
---------------------------	--	--	---------------------	---------------------------	--------------------------


County: Gray

Distance and direction from nearest town or city street address of well if located within city?
From Ingalls - 1½ Miles Southwest, 6 Miles South, 3,745 Ft. West & 1,100 Ft. North

2 WATER WELL OWNER: Lloyd Frack Estate

RR#, St. Address, Box # : Route 1 - Box 142

City, State, ZIP Code : Ingalls, Kansas 67853

Board of Agriculture, Division of Water Resources
Application Number: 222483 LOCATE WELL'S LOCATION WITH
AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 255 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 159½ ft. below land surface measured on mo/day/yr 6-14-93

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 30 in. to 255 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)
 2 PVC 4 ABS

5 Wrought iron

6 Asbestos-Cement
7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued Clamped

Welded X

Threaded

Blank casing diameter: 16 in. to 190 in. to ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface: 12 in., weight: 42.05 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel
 2 Brass 4 Galvanized steel

5 Fiberglass

6 Concrete tile

7 PVC

8 RMP (SR)

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot
 2 Louvered shutter 4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS: From: 190 ft. to 255 ft., From: ft. to ft., From: ft. to ft.

From: ft. to ft., From: ft. to ft., From: ft. to ft.

GRAVEL PACK INTERVALS: From: 20 ft. to 255 ft., From: ft. to ft., From: ft. to ft.

From: ft. to ft., From: ft. to ft., From: ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From: 0 ft. to 20 ft., From: ft. to ft., From: ft. to ft., From: ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines
 2 Sewer lines 5 Cess pool
 3 Watertight sewer lines 6 Seepage pit

7 Pit privy

8 Sewage lagoon

9 Feedyard

10 Livestock pens

11 Fuel storage

12 Fertilizer storage

13 Insecticide storage

14 Abandoned water well

15 Oil well/Gas well

16 Other (specify below)

Direction from well? Northwest How many feet? 195 Ft. North & 190 Ft. West

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

See attached log

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-25-93 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 7-20-93 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) *Nora Keller*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.