


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
34° 42' N 105° 48' W		Gray	SE 1/4 SE 1/4 NE 1/4	18	T 27 S R 29 E/W	
2. Distance and direction from nearest town or city: Street address of well location if in city:			3. Owner of well: Paul Yost R.R. or street: City, state, zip code: Montezuma, Kansas 67867			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 9 7/8" Completion date Well depth 247 ft. 12-02-76		
N 1 Mile W E S 1 Mile				7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
5. Type and color of material				From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input checked="" type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
Top soil				0	6	9. Casing: Material PVC Height: Above or below ground Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 2.8 lbs./ft. Dia. 5 in. to 247 ft. depth Wall Thickness: inches or Dia. in. to ft. depth Gauge No. 265
Clay				6	65	10. Screen: Manufacturer's name Jess & Lowell Type PVC Dia. 5" Slot 1/8" Length 40' Set between 112 ft. and 247 ft. ft. and ft. Gravel pack? yes Size range of material 3/16"
Med. to lar. sand & gravel				65	152	11. Static water level: mo./day/yr. 85 ft. below land surface Date 11/24/76
Med. to lar. sand & gravel with sandy clay				152	230	12. Pumping level below land surfaces: 90 ft. after 1 1/2 hrs. pumping 50-60 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 50+ g.p.m.
Med. to lar. sand				230	250	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date
						14. Well head completion: Pitless adapter 12 Inches above grade
						15. Well grouted? yes With: Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: None ft. Direction Type Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
						17. Pump: Installed <input checked="" type="checkbox"/> Not installed Manufacturer's name Customers Windmill Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
(Use a second sheet if needed)						
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Friesen Windmill 252 Business name License No. Address Meade, Kansas 67864 Signed [Signature] Date 12-16-76 Authorized representative		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5