


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County GRAY	Fraction SW 1/4 SW 1/4 SW 1/4	Section number 32	Township number T 27 S	Range number R 29 NW
2. Distance and direction from nearest town or city:	South of Pierceville to 22 mile rd. 9 east, $\frac{1}{2}$ north Street address of well location if in city:				
3. Owner of well:	Paul Yost R.R. or street: Montezuma, Ks. 67867 City, state, zip code:				
4. Locate with "X" in section below:	Sketch map: 				
5. Type and color of material	From	To	6. Bore hole dia. 26 in. Completion date 3-31-76 Well depth 330 ft. 7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary 8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other 9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 331 depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 219 MNC 10. Screen: Manufacturer's name Johnson Division Type: Clav. Dia. 16" Slot/gauze 100 Length 20' Set between 270 ft. and 290 ft. Perf. 120-180 ft. and 230-270 290-330 Gravel pack? Yes Size range of material 21" Down 11. Static water level: mo./day/yr. ft. below land surface Date 12. Pumping level below land surfaces: 121 ft. after 3 hrs. pumping 1300 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1300 g.p.m. 13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No Date 14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade 15. Well grouted? Yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft. 16. Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? Yes <input type="checkbox"/> No 17. Pump: Manufacturer's name Peerless PTC Model number 141C HP 125 Volts Length of drop pipe 240 ft. capacity 1200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other 18. Elevation: Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley 19. Remarks: Used Casing (Use a second sheet if needed)		
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling 208 Business name Address P.O. Box A Garden City, KS License No. Signed <i>[Signature]</i> Date <i>[Signature]</i> Authorized representative					

The Professionals **MINTER-WILSON DRILLING CO.** INCORPORATED

and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

PAUL YOST
Gray County
1-22-76

Location: SW 32-27-29
1/4 Mile West, 1/2 Mile North of Paul Yost house

Static Water Level - 82'

Test #1

0	4	Top Soil
4	19	Brown Sandy Clay
19	47	Fine to Med. Sand
47	71	Brown & white, Sandy Clay
71	95	Fine to Med. Sand & Gravel (loose)
95	112	Fine to Med. Sand & Gravel & Brown Rock (Loose)
112	125	Fine to Med. Sand & Gravel, Smooth Brown & White Rock, Streaks of Clay (10%) Loose
125	168	Fine to Med. Sand & Gravel, Streaks of Clay (10%) Loose
168	188	Brown & Gray Sandy Clay (Tight)
188	230	Brown Clay & Fine Sand Mixture (50%)
230	247	Brown Sandy Clay
247	260	Fine to Med. Sand, Streaks of Clay (15%)
260	305	Fine to Med. Sand & Gravel (Loose)
305	330	Fine to Med. Sand & Gravel, Streaks of Clay (10%) Loose
330	335	Yellow & Gray Clay

TD - 330'