

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

LOCATION OF WATER WELL:	Fraction	NE $\frac{1}{4}$	NE $\frac{1}{4}$	NE $\frac{1}{4}$	Section Number	33	Township Number	T 27 S	Range Number	R 29 E
-------------------------	----------	------------------	------------------	------------------	----------------	----	-----------------	--------	--------------	--------

County: GRAY

Distance and direction from nearest town or city street address of well if located within city?

3 1/2 North, 2 West, 3/4 North of Montezuma, Kansas

WATER WELL OWNER:

Leben Drilling Inc.

RR#, St. Address, Box # :

640 Broadway Plaza Bldg.


Board of Agriculture, Division of Water Resources

City, State, ZIP Code :

Wichita, Ks. 67202

Application Number: _____

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 210 ft. ELEVATION: Upland

Depth(s) Groundwater Encountered 1. Not available ft. 3. ft.

WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr June 14, 1983

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 50. gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8. 7/8.in. to 210 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot X6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No XX. If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:

5 Wrought iron 8 Concrete tile Casing joints: Glued .. XX. Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

XX2 PVC

4 ABS

7 Fiberglass

Threaded

Blank casing diameter 5 in. to ... 170 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 1265

TYPE OF SCREEN OR PERFORATION MATERIAL:

XX7 PVC 10 Asbestos-cement

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

11 Other (specify)

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

5 Gauzed wrapped

XX8 Saw cut

11 None (open hole)

1 Continuous slot

3 Mill slot

6 Wire wrapped

9 Drilled holes

2 Louvered shutter

4 Key punched

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 170 ft. to 210 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 14 ft. to 210 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage XX5 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

100 Feet

Direction from well? East How many feet?

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 80 Fine Sand

8 75 Clay

75 214 05 Med. to Lar. Sand

214 -- 30 Bed Rock

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 14, 1983 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) July 7, 1983

Under the business name of Friesen Windmill & Supply Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

1 27

29

END

SEC.

33

NE 1/4

SE 1/4

SW 1/4

NW 1/4

DP