

SE SW SW


drl

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

ID No.

1 LOCATION OF WATER WELL:		Fraction SE SW SE SW	Section Number 29	Township Number T 27 S	Range Number R 29 E	
Distance and direction from nearest town or city street address of well if located within city? <i>4 N + 3 1/4 W from Montezuma</i>						
2 WATER WELL OWNER:		Dan Johnson				
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources Application Number:				
City, State, ZIP Code : Dodge City, KS 67801						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL ft. ELEVATION:  Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 18.2 ft. below land surface measured on mo/day/yr 3-23-05 Pump test data: Well water was 18.2 ft. after 1 hours pumping 7.0 gpm Est. Yield 50 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No				
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 6 Asbestos-Cement 3 RMP (SR) PVC 4 ABS	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded Threaded		
Blank casing diameter 5 in. to ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or guage No. 20.0						
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass 1 Steel 6 Concrete tile 3 Stainless Steel 2 Brass 4 Galvanized Steel	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		5 Glazed wrapped 1 Continuous slot 6 Wire wrapped 2 Louvered shutter 4 Key punched	7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify) ft.		
SCREEN-PERFORATED INTERVALS: From 240 ft. to 300 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 20 ft. to 300 ft., From ft. to ft.						
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 4 ft. to 20 ft., From ft. to ft., From ft. to ft.	2 Cement grout From ft. to ft., From ft. to ft., From ft. to ft.	3 Bentonite What is the nearest source of possible contamination:	4 Other 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? <i>N</i>		How many feet? <i>100</i>				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	8	sandy top soil	235	300	sand + gravel	
8	15	dark brown clay				
15	21	sand				
21	24	light brown clay				
24	26	sand				
26	38	top clay				
38	55	sand				
55	62	top sandy clay				
62	78	sand + gravel				
78	116	reddish brown clay				
116	130	sand + gravel				
130	170	sandy brown clay				
170	210	sand + gravel				
210	235	brown clay				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>3-24-05</i> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <i>101</i> This Water Well Record was completed on (mo/day/yr) <i>3-15-05</i> under the business name of <i>Bartel Well</i> by (signature) <i>Paul Lee J. Bartel</i>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.						