

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Gray</u>		<u>NE 1/4 NE 1/4 NE 1/4</u>	<u>22</u>	T <u>27</u> S	R <u>29</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>From Montezuma, 5 1/2 miles north, 1 mile west, 1/2 mile north</u>					
2 WATER WELL OWNER: <u>Ben Schmidt</u>					
RR#, St. Address, Box #: <u>22505 11 Rd.</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: <u>Montezuma, KS 67867</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>275</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL <u>132</u> ft. below land surface measured on mo/day/yr <u>12-7-04</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
② PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	
		7 Fiberglass		Threaded	
Blank casing diameter <u>5</u> in. to <u>255</u> ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR-21</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	⑦ PVC	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)	
			9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	⑧ Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	7 Torch cut	9 Drilled holes	
				10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From <u>255</u> ft. to <u>275</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>24</u> ft. to <u>275</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ③ Bentonite 4 Other					
Grout Intervals: From <u>4</u> ft. to <u>24</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	⑭ Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)	
Direction from well? <u>South</u> How many feet? <u>12</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Topsoil			
5	55	Brown clay			
55	185	Coarse sand			
185	210	Brown sandy clay			
210	220	Med. sand			
220	260	Brown sandy clay			
260	275	Coarse sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-7-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>533</u> This Water Well Record was completed on (mo/day/yr) <u>4-28-05</u> under the business name of <u>Jantzen water well Repair</u> by (signature) <u>[Signature]</u>					