

WATER WELL RECORD Form WWC-5

Original Record Correction Change in Well Use

Division of Water Resources App. No.

Well ID

1 LOCATION OF WATER WELL: County: Gray Fraction NW 1/4 SE 1/4 NE 1/4 SE 1/4 Section Number 3 Township Number T 27 S Range Number R 29 E W

2 WELL OWNER: Last Name: Millershaski First: Daryl Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection):

3 LOCATE WELL WITH "X" IN SECTION BOX: N W E S 1 mile 4 DEPTH OF COMPLETED WELL: 505 ft. 5 Latitude: 37.72783 Longitude: 100.47124 Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS Land Survey Topographic Map Online Mapper 6 Elevation: 2751 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in. to 505 ft. Diameter in. to ft. Diameter in. to ft. Casing height above land surface 12 in. Weight lbs./ft. Wall thickness or gauge No. SDR21 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 405 ft. to 505 ft. GRAVEL PACK INTERVALS: From 24 ft. to 505 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 4 ft. to 24 ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? Distance from well? ft.

Table with 6 columns: 10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 3/14/2018 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 533. This Water Well Record was completed on (mo-day-year) 4/30/2018 under the business name of Jantzen Water Well.

Form	WWC5
Contractor	Jantzen Water Well
Well Owner	Daryl Millershaski
Doc ID	1407666

Litholgy

Lithology		
0	70	Brown Sandy Clay
70	100	Medium Sand
100	110	Course Medium Sand
110	140	Brown Sandy Clay
140	160	White Sandy Clay
160	170	Brown Sandy Clay
170	182	Brown Clay
182	233	Course Sand
233	235	Limestone & Shale
235	242	Shale
242	340	Shale & Sandstone layers
340	370	Sandstone (loose)
370	380	Shale
380	410	Sandstone (loose)
410	417	Shale
417	418	Sandstone (loose)
418	505	Sandstone & Shale