

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NW 1/4 NW 1/4 SW 1/4</u>	<u>27</u>	<u>T 27 S</u>	<u>R 3 E/W</u>
Distance and direction from nearest town or city, street address of well if located within city? <u>1000 S. 263rd West</u>					
2 WATER WELL OWNER: <u>Joe Allen</u>					
RR#, St. Address, Box #: <u>P.O. Box 671</u>					
City, State, ZIP Code: <u>Goddard, KS 67052</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>81</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>20</u> ft. 2. <u>81</u> ft. 3. <u>6/17/96</u> ft.			
		WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr <u>6/17/96</u>			
		Pump test data: Well water was <u>12</u> gpm. Well water was <u>81</u> ft. after <u>11</u> hours pumping <u>81</u> gpm			
		Bore Hole Diameter <u>11</u> in. to <u>81</u> ft., and <u>11</u> in. to <u>81</u> ft.			
WELL WATER TO BE USED AS:					
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No <u>X</u>					
5 TYPE OF BLANK CASING USED:					
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> ☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded <u>X</u> ☐ 3 Fiberglass Threaded <u>X</u>					
Blank casing diameter <u>5</u> in. to <u>43</u> ft. Dia. <u>2.60</u> in. to <u>100 PSI</u> ft.					
Casing height above land surface <u>12</u> in., weight <u>2.60</u> lbs./ft. Wall thickness or gauge No. <u>100 PSI</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 10 Asbestos-cement ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) <u>7 PVC</u> ☐ 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 7 Torch cut ☐ 10 Other (specify) <u>81</u>					
SCREEN-PERFORATED INTERVALS: From <u>43</u> ft. to <u>81</u> ft. From <u>20</u> ft. to <u>81</u> ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>81</u> ft. From <u>20</u> ft. to <u>81</u> ft.					
6 GROUT MATERIAL: <u>3</u> 1 Neat cement <u>20</u> 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From <u>20</u> ft. to <u>81</u> ft. From <u>20</u> ft. to <u>81</u> ft.					
What is the nearest source of possible contamination:					
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 2 Sewer lines ☐ 5 Cess pool ☒ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage					
Direction from well? <u>20</u> How many feet? <u>East</u>					
LITHOLOGIC LOG					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	38	clay			
38	42	fine sand			
42	81	shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-19-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>6-20-96</u> under the business name of <u>Weninger Drilling, Inc.</u> by (signature) <u>Kenneth P. Brasser</u>					