

1 LOCATION OF WATER WELL: County: Saline Fraction: SE 1/4 NW 1/4 SE 1/4 Section Number: 1 Township Number: T 27 S Range Number: R 3 E

Distance and direction from nearest town or city: 22002 W. 24th Circle

2 WATER WELL OWNER: Mark & Donna Seiler Board of Agriculture, Division of Water Resources

RR#, St. Address, Box #: 22002 W. 24th Circle Application Number: 95

City, State, ZIP Code: Colwich, KS 66000

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 6-16-99

Depth(s) Groundwater Encountered: 45 ft. below land surface measured on 6-16-99

WELL'S STATIC WATER LEVEL: 45 ft. below land surface measured on 6-16-99

Pump test data: Well water was 20 gpm. Well water was 81 ft. after 11 hours pumping

Est. Yield: 20 gpm. Well water was 81 ft. after 11 hours pumping

Bore Hole Diameter: 11 in. to 81 ft. and 11 in. to 81 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X

Blank casing diameter: 55 in. to 55 ft. Dia. 2.40 in. to 2.40 ft. Dia. 160 lbs./ft. Wall thickness or gauge No. 160psi

Casing height above land surface: 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160psi

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 55 ft. to 95 ft. From 55 ft. to 95 ft.

GRAVEL PACK INTERVALS: From 45 ft. to 95 ft. From 45 ft. to 95 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 45 ft. From 45 ft. to 95 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? North How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	52	clay			
52	95	shale, charcoal green			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-16-99 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 38 This Water Well Record was completed on (mo/day/yr) 7-1-99

under the business name of Weninger Drilling Inc. by (signature) Thane George

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.