

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 NW 1/4 SW 1/4	Section Number 7	Township Number T 27 S	Range Number R 3W E/W
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1656 N. 311th W. Andale, Kansas

WATER WELL OWNER: SIMON, Ron	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 1656 N. 311th W.	Application Number:
CITY, STATE, ZIP CODE: Andale, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 65 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 10/26/1999
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm : Well water was ft. after hours pumping gpm
Bore Hole Diameter 12 in. to 65 ft. and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes submitted	No X ; If yes, mo/day/yr sample was Water Well Disinfected? Yes X No

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Glued X Clamped
2 PVC 4 ABS	7 Fiberglass	SDR-26	Welded
Blank casing Diameter 5 in. to 25 ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height above land surface 12 in., weight 2.35 lbs. / ft.			Wall thickness or gauge No. .214
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
1 Steel 3 Stainless Steel	6 Concrete tile	9 ABS	11 other (specify)
2 Brass 4 Galvanized steel			12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter 4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 25 ft. to 65 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: from 25 ft. to 65 ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement	2 Cement grout	3 Bentonite	4 Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandon water well
1 Septic tank 4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines 5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit	9 Feedyard	13 Insecticide storage	None Apparent

Direction from well?		How many feet?	
FROM	TO	FROM	TO
0	4		
4	21		
21	32		
32	65		
LITHOLOGIC LOG		PLUGGING INTERVALS	
topsoil			
clay			
medium fine sand			
red shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/26/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10/27/99 Under the business name of Harp Well & Pump Service, Inc. by (signature)
--

Todd S. Harp