

1 LOCATION OF WATER WELL: Fraction <u>NE 1/4 NW 1/4 SW 1/4</u> Section Number <u>32</u> Township Number <u>T 27 S</u> Range Number <u>R 3 E</u>			
County: <u>Sedgewick</u> Distance and direction from nearest town or city street address of well if located within city? <u>113 Hibiscus 67050</u>			
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : <u>Mike Long 96</u> Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>96</u> ft. ELEVATION: <u>9-3-084</u> ft.		
	Depth(s) Groundwater Encountered <u>15</u> ft. 2 <u>9-3-084</u> ft. 3 <u>9-3-084</u> ft. WELL'S STATIC WATER LEVEL <u>15</u> ft. below land surface measured on mo/day/yr <u>9-3-084</u> gpm Pump test data: Well water was <u>15</u> ft. after <u>9-3-084</u> hours pumping <u>9-3-084</u> gpm Est. Yield <u>18</u> gpm: Well water was <u>15</u> ft. after <u>9-3-084</u> hours pumping <u>9-3-084</u> gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <u>7 Domestic (lawn & garden)</u> 10 Monitoring well		
	Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected <u>Yes</u> No		
	5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> 7 Fiberglass Threaded <u>X</u>		
	Blank casing diameter <u>5</u> in. to <u>16</u> in. Dia <u>2.40</u> in. to <u>16</u> in. Dia <u>100</u> lbs. Casing height above land surface <u>12</u> in. weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>100</u> ps.		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) <u>100</u> 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) <u>100</u> ft. 7 Torch cut			
SCREEN-PERFORATED INTERVALS: From <u>16</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft.			
GRAVEL PACK INTERVALS: From <u>15</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>35 ft</u> Grout Intervals: From <u>3</u> ft. to <u>15</u> ft. From <u>15</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft. From <u>15</u> ft. to <u>96</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well <u>3 Watertight sewer lines</u> 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>North</u> How many feet? <u>35 ft</u>			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS			
0 3	Top Soil		
3 8	Clay		
8 17	Med Sand		
17 96	Shale		

RECEIVED

OCT 04 2004

BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-3-084 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 318 This Water Well Record was completed on (mo/day/yr) 9-3-084 under the business name of Weninger Drilling Inc. by (signature) [Signature]