WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick  $\mathbf{SW}$ 1/4  $\mathbf{SW}$ 1/4 NE 1/4 36 Т 27 S 3W E/W Distance and direction from nearest town or city street address of well if located within city? 2600 S. 222nd St West Goddard, Kansas BUCKERT, AARON CONTRACTING INC. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: P.O. Box 780405 Wichita, Kansas CITY, STATE: ZIP CODE Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 80 ft **ELEVATION** Depth of groundwater Encountered: ft. ft. ft WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND S JRFACE MEASURED ON mo/day/yr: Pumo test data: Well water was ft. after hours of pumping @ NW NE Est. Yield: apm Well water was ft. after hours of pumping @ gpm ≌ Bore Hole Diameter 12 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample (NO) Was a chemical/bacteriological sample submitted to Department? (YES) submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 45 to ft., Dia. in. ft.. Dia. ft. in. to in to 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1 Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 2. Brass 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 1. Continuous slot 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 80 From to ft., From ft. to ft. to ft., From ft. to 24 GRAVEL PACK INTERVALS: ft. to 80 From ft., From to ft. From to ft., From ft. to ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft 24 ft.. From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Yet 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit How many feet? Direction from well? From Τо LITHOLOGIC LOG From To LITHOLOGIC LOG O topsoil 35 clay 3 35 40 fine sand 40 <u>50</u> medium sand 50 80 gray shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. 10/11/16 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/14/16 by (signature) Todd S. Harp under the business name of Harp Well and Pump Service