KOLAR Document ID: 1482299

		ECORD Correction		WWC-5 ge in Well Use			ion of Wate rces App. N			Well ID			
Original Record Correction Chang 1 LOCATION OF WATER WELL:			Fraction				ion Number Township Num			ge Number			
County:					1/4 1/4	¹ / ₄ T S R				□ E □ W			
						Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:							
City:		1	State:	ZIP:			T						
3 LOCATE WELL WITH "X" IN 4 DEPTH OF COMPLETED WELL:						ft. 5 Latitude :(decimal degrees)							
	ON BOX:		Depth(s) Groundwater Encountered: 1)				8						
	N	2) ft. 3) ft., or 4) Dr WELL'S STATIC WATER LEVEL:				I	Datum: 🗌 WGS 84 🔲 NAD 83 🔲 NAD 27						
			below land surface, measured on (mo-day-yr)				Source for Latitude/Longitude:						
NW	NE		_				(WAAS enabled? ☐ Yes ☐ No)						
		-	Pump test data: Well water was ft. after hours pumping gpm				\Box Land Survey \Box Topographic Map						
W	Wel			water was ft.			□ Online Mapper:						
SW					pumping gpm			6 Elevation:ft. Ground Level TOC					
		Estimated Yield:gpm Bore Hole Diameter:in. tofi				Source: Land Survey GPS Topographic Ma							
	S mile	Dore Hote I	in. to										
7 WELL WATER TO BE USED AS:													
	1. Domestic: 5. □ Public Water Supply: well ID												
				ng: how many wells?			11. Test Hole: well ID						
	$\Box Livestock $ 8. \Box Monitoring: well							12. Geothermal: how many bores?					
	□ Irrigation 9. Environmental Remediation: well ID						a) Closed Loop 🔲 Horizontal 🗌 Vertical						
3. Example Feedlot Air Sparge 4. Industrial Recovery					r Extraction				n Loop □ Surface Discharge □ Inj. of Water r (specify):				
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:													
Water well disinfected? Ves No													
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded													
Casing diameter in. to ft., Diameter in. to ft., Diameter ft.													
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No													
Steel Stainless Steel PVC Other (Specify)													
□ Brass □ Galvanized Steel □ None used (open hole)													
SCREEN OR PERFORATION OPENINGS ARE:													
□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify) □ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)													
				n ft. to			· •			ft. to	ft.		
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.													
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other													
		e contaminati	on: No	potential source of co	ontamination	with	in 200 ft.		11. 10	II.			
Septic Septic			Lateral Line	es 🗌 Pit Privy		ΠL	ivestock Pe			ide Storage			
Sewer			Cess Pool	Sewage I			uel Storage				Well		
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well □ Other (Specify)													
Direction fro	om well?			Distance from	well?								
10 FROM	TO	I	ITHOLOG	GIC LOG	FROM	I	ТО	LIT	HO. LOG (cont.) or	PLUGGIN	G INTERVALS		
	T					-+							
					Notes:								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, a reconstructed, or plugged													
under mv i	urisdiction a	nd was compl	eted on (m	5 CEKTIFICATI no-day-year)	איז inis w	ater v nd th	wen was <u> </u> is record	co is tru	nstructed, $[]$ reco	nstructed, v knowled	e and belief		
				no-day-year) 									
under the business name of													
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.													
Visit us at	nttp://www.kdhe	eks.gov/waterwel	l/index.html							KS	SA 82a-1212		