


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 24 Township Number T 27 S Range Number R 3 (W)
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? See Below.

2 WATER WELL OWNER: Mike Milford
 RR#, St. Address, Box #: 22311 W. 4th No
 City, State, ZIP Code: Goddard KS 67052
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 48 ft.
 Depth(s) Groundwater Encountered 1. 48 ft. 2. 70 ft. 3. 12 ft.
 WELL'S STATIC WATER LEVEL 36 ft. below land surface measured on 6-10-91 mo/day/yr
 Pump test data: Well water was 70 ft. after 12 hours pumping 12 gpm
 Est. Yield 12-15 gpm: Well water was 70 ft. after 12 hours pumping 12 gpm
 Bore Hole Diameter 11 in. to 80 ft., and 80 in. to 80 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued X Clamped X
☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded X
☐ 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 30 ft., Dia. 2 in. to 60 lbs./ft. Wall thickness or gauge No. 160 PVC
 Casing height above land surface 12 in., weight 2 lbs./ft.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 11 Other (specify)
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 80 ft., From 23 ft. to 80 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 80 ft., From 23 ft. to 80 ft.

6 GROUT MATERIAL: ☒ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 23 ft., From 23 ft. to 80 ft., From 23 ft. to 80 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☒ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? SE How many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	39	Clay			
39	80	Green & Charcoal shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-10-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 1318 This Water Well Record was completed on (mo/day/yr) 6-24-91 under the business name of Wagner's Well by (signature) [Signature]