


1 LOCATION OF WATER WELL: County: Edgwick Fraction: SW 1/4 SW 1/4 NW 1/4 Section Number: 31 Township Number: T 27 S Range Number: R 3 E 0
Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: RICHARD KLINE
RR#, St. Address, Box #: 2154 Koenigs
City, State, ZIP Code: Garden Plain MO 67050
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION: 7-21-90
 Depth(s) Groundwater Encountered 1. 28 ft. 2. 28 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 7-21-90
 Pump test data: Well water was 28 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 28 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter: 11 in. to 58 ft. and 58 in. to 58 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☒ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 5 in. to 38 ft. Dia. 1.59 lbs./ft. Wall thickness or gauge No. 50R-26
 Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 50R-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 50R-26
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 50R-26
 SCREEN-PERFORATED INTERVALS: From 38 ft. to 58 ft. From 38 ft. to 58 ft.
 From 38 ft. to 58 ft. From 38 ft. to 58 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 58 ft. From 23 ft. to 58 ft.
 From 23 ft. to 58 ft. From 23 ft. to 58 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft.
 What is the nearest source of possible contamination:
☒ Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
☒ Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
☒ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	6	clay			
6	32	fine sand			
32	34	clay			
34	48	gravel			
48	58	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-21-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-28-90 under the business name of Weninger Pump by (signature) [Signature]