

1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 NW 1/4 Section Number 31 Township Number T 27 S Range Number R 3 E
 County: Edgewood Distance and direction from nearest town or city street address of well if located within city?
311 Kraus St. Garden Plain KS.

2 WATER WELL OWNER: Ray Fisher 67050
 RR#, St. Address, Box #: 311 KRAUS Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Garden Plain KS Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
X	
SW	SE

4 DEPTH OF COMPLETED WELL: 61 ft. ELEVATION: 28 ft.
 Depth(s) Groundwater Encountered 1. 28 ft. 2. 30 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 9-24-89
 Pump test data: Well water was 30 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 30 gpm: Well water was 30 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 61 ft., and 61 in. to 61 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded SDR-26
 2 PVC ☐ 4 ABS ☐ 7 Fiberglass ☐ Threaded
 Blank casing diameter 5 in. to 41 ft., Dia 41 in. to 61 ft., Dia 61 in. to 61 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☒ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☒ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 7 Torch cut ☐ 10 Other (specify) ☐
 SCREEN-PERFORATED INTERVALS: From 41 ft. to 61 ft., From 61 ft. to 61 ft.
 From 61 ft. to 61 ft., From 61 ft. to 61 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 61 ft., From 61 ft. to 61 ft.
 From 61 ft. to 61 ft., From 61 ft. to 61 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
 Grout intervals: From 3 ft. to 23 ft., From 23 ft. to 61 ft., From 61 ft. to 61 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage ☐ 14 How many feet? 60

Direction from well? East.

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soi			
2	10	clay			
10	30	fine sand			
30	41	clay			
41	51	med sand			
51	61	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-24-89 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 310 This Water Well Record was completed on (mo/day/yr) 10-16-89
 under the business name of Wenger, Dully by (signature) Fisher